



US006675498B1

(12) **United States Patent**
Ellis, III

(10) **Patent No.:** **US 6,675,498 B1**
(45) **Date of Patent:** **Jan. 13, 2004**

- (54) **SHOE SOLE STRUCTURES**
- (75) Inventor: **Frampton E. Ellis, III**, Arlington, VA (US)
- (73) Assignee: **Anatomic Research, Inc.**, Arlington, VA (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
- (21) Appl. No.: **08/482,838**
- (22) Filed: **Jun. 7, 1995**

1,458,446 A	6/1923	Shaeffer
1,622,860 A	3/1927	Cutler
1,639,381 A	8/1927	Manelas
1,701,260 A	2/1929	Fischer
1,735,986 A	11/1929	Wray
1,853,034 A	4/1932	Bradley
2,120,987 A	6/1938	Murray
2,147,197 A	2/1939	Glidden
2,155,166 A	4/1939	Kraft
2,170,652 A	8/1939	Brennan
2,179,942 A	11/1939	Lyne
2,328,242 A	8/1943	Witherill
2,433,329 A	12/1947	Adler et al.
2,434,770 A	1/1948	Lutey
2,627,676 A	2/1953	Hack
2,718,715 A	9/1955	Spilman
2,814,133 A	11/1957	Herbst

Related U.S. Application Data

- (63) Continuation of application No. 08/452,490, filed on May 30, 1995, now Pat. No. 6,360,453, which is a continuation of application No. 08/142,120, filed on Oct. 28, 1993, now abandoned, which is a continuation of application No. 07/830,747, filed on Feb. 7, 1992, now abandoned, which is a continuation of application No. 07/416,478, filed on Oct. 3, 1989, now abandoned, and a continuation of application No. 08/162,962, filed on Dec. 8, 1993, now Pat. No. 5,544,429, which is a continuation of application No. 07/930,469, filed on Aug. 20, 1992, now Pat. No. 5,317,819, which is a continuation of application No. 07/239,667, filed on Sep. 2, 1988, now abandoned, and a continuation of application No. 07/492,360, filed on Mar. 9, 1990, now Pat. No. 4,989,349, which is a continuation of application No. 07/219,387, filed on Jul. 15, 1988, now abandoned.

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

AT	200963	5/1958
CA	1 138 194	12/1982

(List continued on next page.)

OTHER PUBLICATIONS

Originally filed specification for U.S. patent application No. 08/648,792, filed Aug. 28, 2000.
Originally filed specification for U.S. patent application No. 08/462,531, filed Jun. 5, 1995.

(List continued on next page.)

Primary Examiner—Anthony D. Stashick

(74) *Attorney, Agent, or Firm*—Finnegan & Henderson et al.

- (51) **Int. Cl.**⁷ **A43B 13/14**
- (52) **U.S. Cl.** **36/25 R; 36/30 R; 36/31; 36/88; 36/114**
- (58) **Field of Search** **36/32 R, 25 R, 36/30 R, 31, 114, 88, 91, 28, 163, 116, 11.5, 11**

(57) **ABSTRACT**


A shoe having a sole contour which follows a theoretically ideal stability plane as a basic concept, but which deviates outwardly therefrom to provide greater than natural stability. Thickness variations outwardly from the stability plane are disclosed, along with density variations to achieve a similar greater than natural stability.

(56) **References Cited**

U.S. PATENT DOCUMENTS

288,127 A	11/1883	Shepard
532,429 A	1/1895	Rogers
1,283,335 A	10/1918	Shillcock
1,289,106 A	12/1918	Bullock

20 Claims, 8 Drawing Sheets



U.S. PATENT DOCUMENTS

3,005,272 A	10/1961	Shelare et al.	4,455,765 A	6/1984	Sjöswärd
3,100,354 A	8/1963	Lombard et al.	4,455,767 A	6/1984	Bergmans
3,110,971 A	11/1963	Chang	4,468,870 A	9/1984	Sternberg
3,305,947 A	2/1967	Kalsoy	4,484,397 A	11/1984	Curley, Jr.
3,308,560 A	3/1967	Jones	4,494,321 A	1/1985	Lawlor
3,416,174 A	12/1968	Novitske	4,505,055 A	3/1985	Bergmans
3,512,274 A	5/1970	McGrath	4,506,462 A	3/1985	Cavanagh
3,535,799 A	10/1970	Onitsuka	4,521,979 A	6/1985	Blaser
3,806,974 A	4/1974	Di Paolo	4,527,345 A	7/1985	Lopez Lopez
3,824,716 A	7/1974	Di Paolo	4,542,598 A	9/1985	Misevich et al.
3,863,366 A	2/1975	Auberry et al.	4,546,559 A	10/1985	Dassler
3,958,291 A	5/1976	Spier	4,557,059 A	12/1985	Misevich et al.
3,964,181 A	* 6/1976	Holcombe, Jr. 36/25 R X	4,559,723 A	* 12/1985	Hamy et al. 36/30 R X
3,997,984 A	12/1976	Hayward	4,559,724 A	12/1985	Norton
4,003,145 A	1/1977	Liebscher et al.	4,561,195 A	12/1985	Onoda et al.
4,030,213 A	6/1977	Daswick	4,577,417 A	3/1986	Cole
4,068,395 A	1/1978	Senter	4,578,882 A	4/1986	Talarico, II
4,083,125 A	4/1978	Benseler et al.	4,580,359 A	4/1986	Kurrash et al.
4,096,649 A	6/1978	Saurwein	4,624,061 A	11/1986	Wezel et al.
4,098,011 A	7/1978	Bowerman et al.	4,624,062 A	11/1986	Autry
4,128,951 A	12/1978	Tansill	4,641,438 A	2/1987	Laird et al.
4,141,158 A	2/1979	Benseler et al.	4,642,917 A	2/1987	Ungar
4,145,785 A	3/1979	Lacey	4,651,445 A	3/1987	Hannibal
4,149,324 A	4/1979	Lesser et al.	4,670,995 A	6/1987	Huang
4,161,828 A	7/1979	Benseler et al.	4,676,010 A	6/1987	Cheskin
4,161,829 A	7/1979	Wayser	4,694,591 A	* 9/1987	Banich et al. 36/30 R X
4,170,078 A	10/1979	Moss	4,697,361 A	10/1987	Ganter et al.
4,183,156 A	1/1980	Rudy	D293,275 S	12/1987	Bua
4,194,310 A	3/1980	Bowerman	4,715,133 A	12/1987	Hartjes et al.
4,217,705 A	8/1980	Donzis	4,724,622 A	2/1988	Mills
4,219,945 A	9/1980	Rudy	D294,425 S	3/1988	Le
4,223,457 A	9/1980	Borgeas	4,727,660 A	3/1988	Bernhard
4,227,320 A	10/1980	Borgeas	4,730,402 A	* 3/1988	Norton et al. 36/30 R
4,235,026 A	11/1980	Plagenhoef	4,731,939 A	3/1988	Parracho et al.
4,240,214 A	12/1980	Sigle et al.	4,747,220 A	5/1988	Autry et al.
4,241,523 A	12/1980	Daswick	D296,149 S	6/1988	Diaz
4,245,406 A	1/1981	Landay et al.	D296,152 S	6/1988	Selbiger
4,250,638 A	2/1981	Linnemann	4,748,753 A	6/1988	Ju
4,258,480 A	3/1981	Famolare, Jr.	4,754,561 A	7/1988	Dufour
4,259,792 A	4/1981	Halberstadt	4,756,098 A	7/1988	Boggia
4,262,433 A	4/1981	Hagg et al.	4,757,620 A	* 7/1988	Tiitola 36/30 R X
4,263,728 A	4/1981	Frecentese	4,759,136 A	7/1988	Stewart et al.
4,266,349 A	5/1981	Schmohl	4,768,295 A	9/1988	Ito
4,268,980 A	5/1981	Gudas	4,785,557 A	11/1988	Kelley et al.
4,271,606 A	6/1981	Rudy	4,817,304 A	4/1989	Parker et al.
4,272,858 A	6/1981	Hlustik	4,827,631 A	5/1989	Thornton
4,274,211 A	6/1981	Funck	4,833,795 A	5/1989	Diaz
4,297,797 A	11/1981	Meyers	4,837,949 A	6/1989	Dufour
4,302,892 A	12/1981	Adamik	4,854,057 A	8/1989	Misevich et al.
4,305,212 A	12/1981	Coomer	4,858,340 A	* 8/1989	Pasternak 36/30 R X
4,308,671 A	1/1982	Bretschneider	4,866,861 A	9/1989	Noone
4,309,832 A	1/1982	Hunt	4,876,807 A	10/1989	Tittola et al.
4,316,332 A	2/1982	Giese et al.	4,890,398 A	1/1990	Thomasson
4,316,335 A	2/1982	Giese et al.	4,906,502 A	3/1990	Rudy
4,319,412 A	3/1982	Muller et al.	4,922,631 A	5/1990	Anderie
4,322,895 A	4/1982	Hockerson	4,934,070 A	6/1990	Mauger
4,335,529 A	6/1982	Badalamenti	4,934,073 A	6/1990	Robinson
4,340,626 A	7/1982	Rudy	4,947,560 A	8/1990	Fuerst et al.
4,342,161 A	8/1982	Schmohl	4,949,476 A	8/1990	Anderie
4,348,821 A	9/1982	Daswick	4,982,737 A	1/1991	Guttman
4,354,319 A	10/1982	Block et al.	4,989,349 A	2/1991	Ellis
4,361,971 A	12/1982	Bowerman	D315,634 S	3/1991	Yung-Mao
4,366,634 A	1/1983	Giese et al.	5,010,662 A	4/1991	Dabuzhsky et al.
4,370,817 A	2/1983	Ratanangsu	5,014,449 A	5/1991	Richard et al.
4,372,059 A	* 2/1983	Ambrose 36/30 R X	5,024,007 A	6/1991	DuFour
4,398,357 A	8/1983	Batra	5,025,573 A	6/1991	Giese et al.
4,399,620 A	8/1983	Funck	5,052,130 A	10/1991	Barry et al.
4,449,306 A	* 5/1984	Cavanagh 36/30 R	5,077,916 A	1/1992	Benteau
4,451,994 A	6/1984	Fowler	5,079,856 A	1/1992	Truelsen
4,454,662 A	6/1984	Stubblefield	5,092,060 A	3/1992	Frachey et al.
			5,131,173 A	7/1992	Anderie

5,224,280 A 7/1993 Preman et al.
 5,224,810 A 7/1993 Pitkin
 5,237,758 A 8/1993 Zachman
 5,317,819 A 6/1994 Ellis
 5,543,194 A 8/1996 Rudy
 5,544,429 A 8/1996 Ellis
 5,909,948 A 6/1999 Ellis, III
 6,115,941 A 9/2000 Ellis, III
 6,115,945 A 9/2000 Ellis, III
 6,163,982 A 12/2000 Ellis, III

WO WO 91/04683 4/1991
 WO WO 91/05491 5/1991
 WO WO 91/10377 7/1991
 WO WO 91/11124 8/1991
 WO WO 91/11924 8/1991
 WO WO 91/19429 12/1991
 WO WO 92/07483 5/1992
 WO WO 92/18024 10/1992
 WO WO 93/13928 7/1993
 WO WO 94/03080 2/1994
 WO WO 97/00029 1/1997
 WO WO 00/64293 11/2000

FOREIGN PATENT DOCUMENTS

CA 1 176 458 10/1984
 DE B23257 VII/71a 5/1956
 DE 1 888 119 2/1964
 DE 1 287 477 1/1969
 DE 1 290 844 3/1969
 DE 1 685 260 10/1971
 DE 27 06 645 8/1978
 DE 27 37 765 3/1979
 DE 28 05 426 8/1979
 DE 30 24 587 A1 1/1982
 DE 32 45 182 5/1983
 DE 33 17 462 10/1983
 DE 36 29 245 3/1988
 EP 0 048 965 4/1982
 EP 0 069 083 1/1983
 EP 0 083 449 7/1983
 EP 0 130 816 1/1985
 EP 0 185 781 7/1986
 EP 0 206 511 12/1986
 EP 0 213 257 3/1987
 EP 0 215 974 4/1987
 EP 0 238 995 9/1987
 EP 0 260 777 3/1988
 EP 0 301 331 2/1989
 EP 0 329 391 8/1989
 EP 0 410 087 1/1991
 FR 602.501 3/1926
 FR 925.961 9/1947
 FR 1.004.472 3/1952
 FR 1.323.455 2/1963
 FR 2 006 270 11/1971
 FR 2 261 721 9/1975
 FR 2 511 850 3/1983
 FR 2 622 411 5/1989
 GB 16143 2/1892
 GB 9591 11/1913
 GB 764956 1/1957
 GB 807305 1/1959
 GB 2 023 405 1/1980
 GB 2 039 717 8/1980
 GB 2 136 670 9/1984
 JP 39-15597 8/1964
 JP 45-5154 3/1970
 JP 50-71132 11/1975
 JP 57-139333 8/1982
 JP 59-23525 7/1984
 JP 61-55810 4/1986
 JP 61-167810 10/1986
 JP 1-195803 8/1989
 JP 3-85102 4/1991
 JP 4-279102 10/1992
 JP 5-123204 5/1993
 NZ 189890 9/1981
 WO WO 87/07480 12/1987
 WO WO 88/08263 11/1988
 WO WO 89/06500 7/1989
 WO WO 90/00358 1/1990
 WO WO 91/00698 1/1991
 WO WO 91/03180 3/1991

OTHER PUBLICATIONS

Originally filed specification for U.S. patent application No. 08/473,212, filed Jun. 7, 1995.

Originally filed specification for U.S. patent application No. 08/477,640, filed Jun. 7, 1995.

Originally filed specification for U.S. patent application No. 08/033,468, filed Mar. 18, 1993.

Originally filed specification for U.S. patent application No. 08/452,490, filed May 30, 1995, and 08/473,974 filed Jun. 7, 1995.

Originally filed specification for U.S. patent application No. 08/479,776, filed Jun. 7, 1995.

Originally filed specification for U.S. patent application No. 09/908,688, filed Jul. 20, 2001.

Williams, "Walking on Air," *Case Alumnus*, Fall 1989, vol. LXVII, No. 6, pp. 4-8.

Brooks advertisement, *Runner's World*, Jun. 1989, p. 56+3pp.

German description of adidas badminton shoe (top row, left), pre 1989(?).

Nigg et al., "Influence of Heel Flare and Midssole Construction on Pronation, Supination, and Impact Forces for Heel-Toe Running," *International Journal of Sport Biomechanics*, 1988, vol. 4, No. 3, pp. 205-219.

Nigg et al., "The influence of lateral heel flare of running shoes on pronation and impact forces," *Medicine and Science in Sports and Exercise*, ©1987, vol. 19, No. 3, pp. 294-302.

The Reebok Lineup, Fall 1987, 2 pages.

Cavanagh et al., "Biological Aspects of Modeling Shoe/Foot Interaction During Running," *Sport Shoes and Playing Surfaces: Biomechanical Proper ties*, Champaign, IL, ©1984, pp. 24-25, 32-35, and 46-47.

Blechs Schmidt, "The Structure of the Calcaneal Padding," *Foot & Ankle*, ©1982, Official Journal of the American Orthopaedic Foot Society, Inc., pp. 260-283.

Cavanagh, *The Running Shoe Book*, Mountain View, CA, ©1980, pp. 176-180.

Ellis, III, *Executive Summary*1, two pages with Figures I-VII attached.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4




FIG. 6




FIG. 7




FIG. 5




FIG. 8




FIG. 9




FIG. 10




FIG. II




FIG. 12




FIG. 13




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 15A




FIG. 15D




FIG. 15B




FIG. 15E




FIG. 15C





FIG. 15F



SHOE SOLE STRUCTURES**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of Ser. No. 08/452,490 filed on May 30, 1995 (Atty. Dkt. ELL-004/CON3), which in turn is a continuation of Ser. No. 08/142,120 filed on Oct. 28, 1993, now abandoned, which is a continuation of Ser. No. 07/830,747 filed on Feb. 7, 1992, now abandoned which is a continuation of Ser. No. 416,478 filed Oct. 3, 1989, now abandoned and application Ser. No. 08/162,962 filed Dec. 8, 1993, now U.S. Pat. No. 5,544,429 which is a continuation of Ser. No. 07/930,469 filed Aug. 20, 1992, now U.S. Pat. No. 5,317,819 issued Jun. 7, 1994 which is a continuation of Ser. No. 07/239,667 filed Sep. 2, 1988, now abandoned and application Ser. No. 07/492,360, filed Mar. 9, 1990, now U.S. Pat. No. 4,989,349 issued Feb. 5, 1991 which is a continuation of Ser. No. 07/219,387, filed Jul. 15, 1988, now abandoned.

BACKGROUND OF THE INVENTION

This invention relates generally to the structure of shoes. More specifically, this invention relates to the structure of running shoes. Still more particularly, this invention relates to variations in the structure of such shoes having a sole contour which follows a theoretically ideal stability plane as a basic concept, but which deviates therefrom outwardly, to provide greater than natural stability. Still more particularly, this invention relates to the use of structures approximating, but increasing beyond, a theoretically ideal stability plane to provide greater than natural stability for an individual whose natural foot and ankle biomechanical functioning having been degraded by a lifetime use of flawed existing shoes.

Existing running shoes are unnecessarily unsafe. They seriously disrupt natural human biomechanics. The resulting unnatural foot and ankle motion leads to what are abnormally high levels of running injuries.

Proof of the natural effect of shoes has come quite unexpectedly from the discovery that, at the extreme end of its normal range of motion, the unshod bare foot is naturally stable, almost unsprainable, while the foot equipped with any shoe, athletic or otherwise, is artificially unstable and abnormally prone to ankle sprains. Consequently, ordinary ankle sprains must be viewed as largely an unnatural phenomena, even though fairly common. Compelling evidence demonstrates that are stability of bare feet is entirely different from the stability of shoe-equipped feet.

The underlying cause of the universal instability of shoes is a critical but correctable design flaw. That hidden flaw, so deeply ingrained in existing shoe designs, is so extraordinarily fundamental that it has remained unnoticed until now. The flaw is revealed by a novel new biomechanical test, one that is unprecedented in its simplicity. The test simulates a lateral ankle sprain while standing stationary. It is easy enough to be duplicated and verified by anyone; it only takes a few minutes and requires no scientific equipment or expertise.

The simplicity of the test belies its surprisingly convincing results. It demonstrates an obvious difference in stability between a bare foot and a running shoe, a difference so unexpectedly huge that it makes an apparently subjective test clearly objective instead. The test proves beyond doubt that all existing shoes are unsafely unstable.

The broader implications of this uniquely unambiguous discovery are potentially far-reaching. The same fundamen-

tal flaw in existing shoes that is glaringly exposed by the new test also appears to be the major cause of chronic overuse injuries, which are unusually common in running, as well as other sport injuries. It causes the chronic injuries in the same way it causes ankle sprains; that is, by seriously disrupting natural foot and ankle biomechanics.

The applicant has introduced into the art the concept of a theoretically ideal stability plane as a structural basis for shoe sole designs. That concept as implemented into shoes such as street shoes and athletic shoes is presented in pending U.S. application Ser. Nos. 07/219,387, filed on Jul. 15, 1988; 07/239,667, filed on Sep. 2, 1988; and 07/400,714, filed an Aug. 30, 1989, as well as in PCT Application No. PCT/US89/03076 filed on Jul. 14, 1989. The purpose of the theoretically ideal stability plane as described in these applications was primarily to provide a natural design that allows for natural foot and ankle biomechanics as close as possible to that between the foot and the ground, and to avoid the serious interference with natural foot and ankle biomechanics inherent in existing shoes.

This new invention is a modification of the inventions disclosed and claimed in the earlier applications and develops the application of the concept of the theoretically ideal stability plane to other shoe structures. As such, it presents certain structural ideas which deviate outwardly from the theoretically ideal stability plane to compensate for faulty foot biomechanics caused by the major flaw in existing shoe designs identified in the earlier patent applications.

The shoe sole designs in this application are based on a recognition that lifetime use of existing shoes, the unnatural design of which is innately and seriously flawed, has produced actual structural changes in the human foot and ankle. Existing shoes thereby have altered natural human biomechanics in many, if not most, individuals to an extent that must be compensated for in an enhanced and therapeutic design. The continual repetition of serious interference by existing shoes appears to have produced individual biomechanical changes that may be permanent, so simply removing the cause is not enough. Treating the residual effect must also be undertaken.

Accordingly, it is a general object of this invention to elaborate upon the application of the principle of the theoretically ideal stability plane to other shoe structures.

It is still another object of this invention to provide a shoe having a sole contour which deviates outwardly in a constructive way from the theoretically ideal stability plane.

It is another object of this invention to provide a sole contour having a shape naturally contoured to the shape of a human foot, but having a shoe sole thickness which is increases somewhat beyond the thickness specified by the theoretically ideal stability plane.

It is another object of this invention to provide a naturally contoured shoe sole having a thickness somewhat greater than mandated by the concept of a theoretically ideal stability plane, either through most of the contour of the sole, or at preselected portions of the sole.

It is yet another object of this invention to provide a naturally contoured shoe sole having a thickness which approximates a theoretically ideal stability plane, but which varies toward either a greater thickness throughout the sole or at spaced portions thereof, or toward a similar but lesser thickness.

These and other objects of the invention will become apparent from a detail description of the invention which follows taken with the accompanying drawings.

BRIEF SUMMARY OF THE INVENTION

Directed to achieving the aforementioned objects and to overcoming problems with prior art shoes, a shoe according

to the invention comprises a sole having at least a portion thereof following approximately the contour of a theoretically ideal stability plane, preferably applied to a naturally contoured shoe sole approximating the contour of a human foot.

In another aspect, the shoe includes a naturally contoured sole structure exhibiting natural deformation which closely parallels the natural deformation of a foot under the same load, and having a contour which approximates, but increases beyond the theoretically ideal stability plane. When the shoe sole thickness is increased beyond the theoretically ideal stability plane, greater than natural stability results; when thickness is decreased, greater than natural motion results.

In a preferred embodiment, such variations are consistent through all frontal plane cross sections so that there are proportionally equal increases to the theoretically ideal stability plane from the front to back. In alternative embodiments, the thickness may increase, then decrease at respective adjacent locations, or vary in other thickness sequences.

The thickness variations may be symmetrical on both sides, or asymmetrical, particularly since it may be desirable to provide greater stability for the medial side than the lateral side to compensate for common pronation problems. The variation pattern of the right shoe can vary from that of the left shoe. Variation in shoe sole density or bottom sole tread can also provided reduced but similar effects.

These and other features of the invention will become apparent from the detailed description of the invention which follows.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows, in frontal plane cross section at the heel portion of a shoe, the applicant's prior invention of a shoe sole with naturally contoured sides based on a theoretically ideal stability plane.

FIG. 2 shows, again in frontal plane cross section, the most general case of the applicant's prior invention, a fully contoured shoe sole that follows the natural contour of the bottom of the foot as well as its sides, also based on the theoretically ideal stability plane.

FIG. 3 as seen in FIGS. 3A to 3C in frontal plane cross section at the heel shows the applicant's prior invention for conventional shoes, a quadrant-sided shoe sole, based on a theoretically ideal stability plane.

FIG. 4 shows a frontal plane cross section at the heel portion of a shoe with naturally contoured sides like those of FIG. 1, wherein a portion of the shoe sole thickness is increased beyond the theoretically ideal stability plane.

FIG. 5 is a side view similar to FIG. 4, but of a shoe with fully contoured sides wherein the sole thickness increases with increasing distance from the center line of the ground-engaging portion of the sole.

FIG. 7 is a view similar to FIGS. 4 to 6 wherein the sole thicknesses vary in diverse sequences.

FIG. 8 is a frontal plane cross section showing a density variation in the midsole.

FIG. 9 is a view similar to FIG. 8 wherein the firmest density material is at the outermost edge of the midsole contour.

FIG. 10 is a view similar to FIGS. 8 and 9 showing still another density variation, one which is asymmetrical.

FIG. 11 shows a variation in the thickness of the sole for the quadrant embodiment which is greater than a theoretically ideal stability plane.

FIG. 12 shows a quadrant embodiment as in FIG. 11 wherein the density of the sole varies.

FIG. 13 shows a bottom sole tread design that provides a similar density variation as that in FIG. 10.

FIG. 14 shows embodiments like FIGS. 1 through 3 but wherein a portion of the shoe sole thickness is decreased to less than the theoretically ideal stability plane.

FIG. 15 show embodiments with sides both greater and lesser than the theoretically ideal stability plane.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIGS. 1, 2, and 3 show frontal plane cross sectional views of a shoe sole according to the applicant's prior inventions based on the theoretically ideal stability plane, taken at about the ankle joint to show the heel section of the shoe. FIGS. 4 through 13 show the same view of the applicant's enhancement of that invention. The reference numerals are like those used in the prior pending applications of the applicant mentioned above and which are incorporated by reference for the sake of completeness of disclosure, if necessary. In the figures, a foot 27 is positioned in a naturally contoured shoe having an upper 21 and a sole 28. The sole includes a heel lift or wedge 38 and combined midsole and outsole 39. The shoe sole normally contacts the ground 43 at about the lower central heel portion thereof, as shown in FIG. 4. The concept of the theoretically ideal stability plane, as developed in the prior applications as noted, defines the plane 51 in terms of a locus of points determined by the thickness (s) of the sole. The thickness (s) of the sole at a particular location is measured by the length of a line extending perpendicular to a line tangent to the sole inner surface at the measured location, all as viewed in a frontal plane cross section of the sole. See, for example, FIGS. 1, 2, and 4-7. This thickness (s) may also be referred to as a "radial thickness" of the shoe sole.

FIG. 1 shows, in a rear cross sectional view, the application of the prior invention showing the inner surface of the shoe sole conforming to the natural contour of the foot and the thickness of the shoe sole remaining constant in the front plane, so that the outer surface coincides with the theoretically ideal stability plane.

FIG. 2 shows a fully contoured shoe sole design of the applicant's prior invention that follows the natural contour of all of the foot, the bottom as well as the sides, while retaining a constant shoe sole thickness in the frontal plane.

The fully contoured shoe sole assumes that the remaining slightly rounded bottom when unloaded will deform under load and flatten just as the human foot bottom is slightly rounded unloaded but flattens under load; therefore, shoe sole material must be of such composition as to allow the natural deformation following that of the foot. The design applies particularly to the heel, but to the rest of the shoe sole as well. By providing the closest match to the natural shape of the foot, the fully contoured design allows the foot to function as naturally as possible. Under load, FIG. 2 would deform by flattening to look essentially like FIG. 1. Seen in this light, the naturally contoured side design in FIG. 1 is a more conventional, conservative design that is a special case of the more general fully contoured design in FIG. 2, which is the closest to the natural form of the foot, but the least conventional. The amount of deformation flattening used in the FIG. 1 design, which obviously varies under different loads, is not an essential element of the applicant's invention.

FIGS. 1 and 2 both show in frontal plane cross sections the essential concept underlying this invention, that theo-

retically ideal stability plane, which is also theoretically ideal for efficient natural motion of all kinds, including running, jogging or walking. FIG. 2 shows the most general case of the invention, the fully contoured design, which conforms to the natural shape of the unloaded foot. For any given individual, the theoretically ideal stability plane **51** is determined, first, by the desired shoe sole thickness (s) in a frontal plane cross section, and, second, by the natural shape of the individual's foot surface **29**.

For the special case shown in FIG. 1, the theoretically ideal stability plane for any particular individual (or size average of individuals) is determined, first, by given frontal plane cross section shoe sole thickness (s); second, by the natural shape of the individual's foot; and, third, by the frontal plane cross section width of the individual's load-bearing footprint **30b**, which is defined as the upper surface of the shoe sole that is in physical contact with and supports the human foot sole.

The theoretically ideal stability plane for the special case is composed conceptually of two parts. Shown in FIG. 1, the first part is a line segment **31b** of equal length and parallel to line **30b** at a constant distance (s) equal to shoe sole thickness. This corresponds to a conventional shoe sole directly underneath the human foot, and also corresponds to the flattened portion of the bottom of the load-bearing foot sole **28b**. The second part is the naturally contoured stability side outer edge **31a** located at each side of the first part, line segment **31b**. Each point on the contoured side outer edge **31a** is located at a distance which is exactly shoe sole thickness (s) from the closest point on the contoured side inner edge **30a**.

In summary, the theoretically ideal stability plane is the essence of this invention because it is used to determine a geometrically precise bottom contour of the shoe sole based on a top contour that conforms to the contour of the foot. This invention specifically claims the exactly determined geometric relationship just described.

It can be stated unequivocally that any shoe sole contour, even of similar contour, that exceeds the theoretically ideal stability plane will restrict natural foot motion, while any less than that plane will degrade naturally stability, in direct proportion to the amount of the deviation. The theoretical ideal was taken to be that which is closest to natural.

FIG. 3 illustrates in frontal plane cross section another variation of the applicant's prior invention that uses stabilizing quadrants **26** at the outer edge of a conventional shoe sole **28b** illustrated generally at the reference numeral **28**. The stabilizing quadrants would be abbreviated in actual embodiments.

FIG. 4 illustrates the applicant's new invention of shoe sole side thickness increasing beyond the theoretically ideal stability plane to increase stability somewhat beyond its natural level. The unavoidable trade-off resulting is that natural motion would be restricted somewhat and the weight of the shoe sole would increase somewhat.

FIG. 4 shows a situation wherein the thickness of the sole at each of the opposed sides is thicker at the portions of the sole **31a** by a thickness which gradually varies continuously from a thickness (s) through a thickness (s+s1), to a thickness (s+s2). Again, as shown in the figures and noted above, the thickness (s) of the sole at a particular location is measured by the length of a line extending perpendicular to a line tangent to the sole inner surface at the measured location, all as viewed in a front plane cross section of the sole. The thickness (s) may also be referred to as a "radial thickness" of the shoe sole.

These designs recognize that lifetime use of existing shoes, the design of which has an inherent flaw that continually disrupts natural human biomechanics, has produced thereby actual structural changes in a human foot and ankle to an extent that must be compensated for. Specifically, one of the most common of the abnormal effects of the inherent existing flaw is a weakening of the long arch of the foot, increasing pronation. These designs therefore modify the applicant's preceding designs to provide greater than natural stability and should be particularly useful to individuals, generally with low arches, prone to pronate excessively, and could be used only on the medial side. Similarly, individuals with high arches and a tendency to over supinate and lateral ankle sprains would also benefit, and the design could be used only on the lateral side. A shoe for the general population that compensates for both weaknesses in the same shoe would incorporate the enhanced stability of the design compensation on both sides.

The new design in FIG. 4, like FIGS. 1 and 2, allows the shoe sole to deform naturally closely paralleling the natural deformation of the barefoot underload; in addition, shoe sole material must be of such composition as to allow the natural deformation following that of the foot.

The new designs retain the essential novel aspect of the earlier designs; namely, contouring the shape of the shoe sole to the shape of the human foot. The difference is that the shoe sole thickness in the frontal plane is allowed to vary rather than remain uniformly constant. More specifically, FIGS. 4, 5, 6, 7, and 11 show, in frontal plane cross sections at the heel, that the shoe sole thickness can increase beyond the theoretically ideal stability plane **51**, in order to provide greater than natural stability. Such variations (and the following variations) can be consistent through all frontal plane cross sections, so that there are proportionately equal increases to the theoretically ideal stability plane **51** from the front of the shoe sole to the back, or that the thickness can vary, preferably continuously, from one frontal plane to the next.

The exact amount of the increase in shoe sole thickness beyond the theoretically ideal stability plane is to be determined empirically. Ideally, right and left shoe soles would be custom designed for each individual based on a biomechanical analysis of the extent of his or her foot and ankle disfunction in order to provide an optimal individual correction. If epidemiological studies indicate general corrective patterns for specific categories of individuals or the population as a whole, then mass-produced corrective shoes with soles incorporating contoured sides exceeding the theoretically ideal stability plane would be possible. It is expected that any such mass-produced corrective shoes for the general population would have thicknesses exceeding the theoretically ideal stability plane by an amount up to 5 or 10 percent, while more specific groups or individuals with more severe disfunction could have an empirically demonstrated need for greater corrective thicknesses on the order of up to 25 percent more than the theoretically ideal stability plane. The optimal contour for the increased thickness may also be determined empirically.

FIG. 5 shows a variation of the enhanced fully contoured design wherein the shoe sole begins to thicken beyond the theoretically ideal stability plane **51** somewhat offset to the sides.

FIG. 7 shows that the thickness can also increase and then decrease; other thickness variation sequences are also possible. The variation in side contour thickness in the new invention can be either symmetrical on both sides or

asymmetrical, particularly with the medial side providing more stability than the lateral side, although many other asymmetrical variations are possible, and the pattern of the right foot can vary from that of the left foot.

FIGS. 8, 9, 10 and 12 show that similar variations in shoe midsole (other portions of the shoe sole area not shown) density can provide similar but reduced effects to the variations in shoe sole thickness described previously in FIGS. 4 through 7. The major advantage of this approach is that the structural theoretically ideal stability plane is retained, so that naturally optimal stability and efficient motion are retained to the maximum extent possible.

The forms of dual and tri-density midsoles shown in the figures are extremely common in the current art of running shoes, and any number of densities are theoretically possible, although an angled alternation of just two densities like that shown in FIG. 8 provides continually changing composite density. However, the applicant's prior invention did not prefer multi-densities in the midsole, since only a uniform density provides a neutral shoe sole design that does not interfere with natural foot and ankle biomechanics in the way that multi-density shoe soles do, which is by providing different amounts of support to different parts of the foot; it did not, of course, preclude such multi-density midsoles. In these figures, the density of the sole material designated by the legend (d1) is firmer than (d) while (d2) is the firmest of the three representative densities shown. In FIG. 8, a dual density sole is shown, with (d) having the less firm density.

It should be noted that shoe soles using a combination both of sole thicknesses greater than the theoretically ideal stability plane and of midsole densities variations like those just described are also possible but not shown.

FIG. 13 shows a bottom sole tread design that provides about the same overall shoe sole density variation as that provided in FIG. 10 by midsole density variation. The less supporting tread there is under any particular portion of the shoe sole, the less effective overall shoe sole density there is, since the midsole above that portion will deform more easily than if it were fully supported.

FIG. 14 shows embodiments like those in FIG. 4 through 13 but wherein a portion of the shoe sole thickness is decreased to less than the theoretically ideal stability plane. It is anticipated that some individuals with foot and ankle biomechanics that have been degraded by existing shoes may benefit from such embodiments, which would provide less than natural stability but greater freedom of motion, and less shoe sole weight add bulk. In particular, it is anticipated that individuals with overly rigid feet, those with restricted range of motion, and those tending to over-supinate may benefit from the FIG. 14 embodiments. Even more particularly, it is expected that the invention will benefit individuals with significant bilateral foot function asymmetry: namely, a tendency toward pronation on one foot and supination on the other foot. Consequently, it is anticipated that this embodiment would be used only on the shoe sole of the supinating foot, and on the inside portion only, possibly only a portion thereof. It is expected that the range less than the theoretically ideal stability plane would be a maximum of about five to ten percent, though a maximum of up to twenty-five percent may be beneficial to some individuals.

FIG. 14A shows an embodiment like FIGS. 4 and 7, but with naturally contoured sides less than the theoretically ideal stability plane. FIG. 14B shows an embodiment like the fully contoured design in FIGS. 5 and 6, but with a shoe sole thickness decreasing with increasing distance from the center portion of the sole. FIG. 14C shows an embodiment

like the quadrant-sided design of FIG. 11, but with the quadrant sides increasingly reduced from the theoretically ideal stability plane.

The lesser-sided design of FIG. 14 would also apply to the FIGS. 8 through 10 and 12 density variation approach and to the FIG. 13 approach using tread design to approximate density variation.

FIGS. 15 A-C show, in cross sections similar to those in pending U.S. application Ser. No. 07/219,387, that with the quadrant-sided design of FIGS. 3, 11, 12 and 14C that it is possible to have shoe sole sides that are both greater and lesser than the theoretically ideal stability plane in the same shoe. The radius of an intermediate shoe sole thickness, taken at (S²) at the base of the fifth metatarsal in FIG. 15B, is maintained constant throughout the quadrant sides of the shoe sole, including both the heel, FIG. 15C, and the forefoot, FIG. 15A, so that the side thickness is less than the theoretically ideal stability plane at the heel and more at the forefoot. Though possible, this is not a preferred approach.

The same approach can be applied to the naturally contoured sides or fully contoured designs described in FIGS. 1, 2, 4 through 10 and 13, but it is also not preferred. In addition, is shown in FIGS. 15 D-F, in cross sections similar to those in pending U.S. application Ser. No. 07/239,667, it is possible to have shoe sole sides that are both greater and lesser than the theoretically ideal stability plane in the same shoe, like FIGS. 15A-C, but wherein the side thickness (or radius) is neither constant like FIGS. 15A-C or varying directly with shoe sole thickness, like in the applicant's pending applications, but instead varying quite indirectly with shoe sole thickness. As shown in FIGS. 15D-F, the shoe sole side thickness varies from somewhat less than shoe sole thickness at the heel to somewhat more at the forefoot. This approach, though possible, is again not preferred, and can be applied to the quadrant sided design, but is not preferred there either.

The foregoing shoe designs meet the objectives of this invention as stated above. However, it will clearly be understood by those skilled in the art that the foregoing description has been made in terms of the preferred embodiments and various changes and modifications may be made without departing from the scope of the present invention which is to be defined by the appended claims.

What is claimed is:

1. An athletic shoe sole for a shoe, comprising:

- a shoe outer sole and a shoe midsole;
- a sole heel area underneath a heel of an intended wearer's foot, a midsole inner surface for supporting a sole of said intended wearer's foot, and a midsole outer surface;
- a midsole central part of the athletic shoe sole located between a midsole medial side portion and a midsole lateral side portion, as viewed in a shoe sole front plane cross-section in the heel area during an unloaded, upright shoe condition;
- the midsole lateral side portion formed by that part of the midsole located lateral of a straight vertical line extending through a sidemost extent of the midsole inner surface of a lateral side of the shoe, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition;
- the midsole medial side portion formed by that part of the midsole located medial of a straight vertical line extending through a sidemost extent of the midsole inner surface of a medial side of the shoe, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition;

said midsole outer surface of said midsole central part comprising a concavely rounded portion, the concavity existing with respect to an inner section of the midsole located directly adjacent to the concavely rounded portion of the midsole outer surface, all as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition;

said midsole inner surface of said midsole central part comprising a convexly rounded portion at least through a midpoint of the midsole inner surface of said midsole central part, the convexity existing with respect to a section of the midsole directly adjacent to the convexly rounded portion of the midsole inner surface, all as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition;

the midsole of at least one of the sole medial side portion and sole lateral side portion extending to above a lowest point of the midsole inner surface, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition;

a radial thickness of at least one of the lateral and medial side portions decreases gradually and continuously from above a sidemost extent of at least one of the lateral and medial side portions to an uppermost point of said at least one of the lateral and medial side portions, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition; and

said shoe midsole comprises midsole material of varying firmness.

2. The shoe sole as set forth in claim 1, wherein said midsole central part comprises a section having at least two material layers, each layer composed of a midsole material of different firmness, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

3. The shoe sole as set forth in claim 1, wherein a midsole firmness of the midsole medial side portion is different from a midsole firmness of the midsole lateral side portion, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

4. The shoe sole as set forth in claim 1, wherein the midsole central part has a varying radial thickness, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

5. The shoe sole as set forth in claim 1, wherein the concavely rounded portion of the midsole outer surface extends through a lowermost portion of the midsole central part, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

6. The shoe sole according to claim 1, wherein the concavely rounded portion of the midsole outer surface extends through a midpoint of the midsole central part, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

7. The shoe sole according to claim 1, wherein the midsole includes three different midsole materials, each with a different firmness.

8. The shoe sole according to claim 1, wherein the midsole extends into both the lateral and medial side portions to above a lowest point of the midsole inner surface, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

9. The shoe sole according to claim 1, wherein the midsole outer surface comprises concavely rounded portions located at both the midsole lateral side portion and the midsole medial side portion, the concavity existing with respect to an inner section of the shoe midsole located

directly adjacent to the concavely rounded portion of the midsole outer surface, all as viewed in the heel area frontal plane cross-section during an unloaded upright shoe condition.

10. The shoe sole as set forth in claim 1, wherein the radial thickness of both of the midsole lateral and medial side portions decreases gradually and continuously from above a sidemost extent of at least one of the lateral and medial side portions to an uppermost point of both of the lateral and medial side portions, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

11. The shoe sole as set forth in claim 1, wherein the concavely rounded portion of the midsole outer surface extends from the midsole central part into one of the midsole lateral and medial side portions, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

12. The shoe sole as set forth in claim 11, wherein the concavely rounded portion of the midsole outer surface extends from the midsole central part into both of the midsole lateral and medial side portions, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

13. The shoe sole as set forth in claim 1, wherein the concavely rounded portion of the midsole outer surface extends from the midsole central part continuously through a sidemost extent of one of the midsole lateral and medial side portions, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

14. The shoe sole as set forth in claim 13, wherein the concavely rounded portion of the midsole outer surface extends from the midsole central part continuously through sidemost extents of both of the midsole lateral and medial side portions, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

15. The shoe sole according to claim 1, wherein the concavely rounded portion of the midsole outer surface extends from the midsole central part to above the lowest point on the midsole inner surface on one of the midsole lateral and medial side portions, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

16. The shoe sole as set forth in claim 15, wherein the concavely rounded portion of the midsole outer surface extends from the midsole central part to above the lowest point on the midsole inner surface of both of the midsole lateral and medial side portions, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

17. The shoe sole according to claim 1, wherein the midsole comprises two different material, one material having a greater radial thickness in one of the lateral and medial side portions than a radial thickness in the midsole central part, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

18. The shoe sole according to claim 17, wherein one of the two different midsole materials has a greater radial thickness in the midsole central part than a radial thickness in one of the lateral and medial side portions, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

19. The shoe sole according to claim 1, wherein the concavely rounded portion of the midsole central part of the midsole outer surface extends to one of said straight vertical

11

lines, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition; and

the convexly rounded portion of the midsole central part of the midsole inner surface extends to one of said straight vertical lines, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

20. The shoe sole according to claim **19**, comprising a concavely rounded portion of the midsole central part of the midsole outer surface extending to the other of said straight

12

vertical lines, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition; and

a convexly rounded portion of the midsole central part of the midsole inner surface extending to the other of said straight vertical lines, as viewed in the heel area frontal plane cross-section during an unloaded, upright shoe condition.

* * * * *