



US006115941A

**United States Patent** [19]  
**Ellis, III**

[11] **Patent Number:** **6,115,941**  
[45] **Date of Patent:** **\*Sep. 12, 2000**

[54] **SHOE WITH NATURALLY CONTOURED SOLE**

[75] Inventor: **Frampton E. Ellis, III**, Arlington, Va.

[73] Assignee: **Anatomic Research, Inc.**, Arlington, Va.

[\*] Notice: This patent is subject to a terminal disclaimer.

[21] Appl. No.: **08/479,779**

[22] Filed: **Jun. 7, 1995**

4,030,213	6/1977	Daswick .	
4,068,395	1/1978	Senter .	
4,096,649	6/1978	Saurwein .	
4,098,011	7/1978	Bowerman et al. .	
4,128,951	12/1978	Tansill .	
4,141,158	2/1979	Benseler et al. .	
4,149,324	4/1979	Lesser et al. .	
4,194,310	3/1980	Bowerman .	
4,217,705	8/1980	Donzis .	
4,245,406	1/1981	Landay et al. .	
4,250,638	2/1981	Linnemann .....	36/11
4,258,480	3/1981	Famolare, Jr. .	

(List continued on next page.)

**Related U.S. Application Data**

[63] Continuation-in-part of application No. 08/162,962, Dec. 8, 1993, Pat. No. 5,544,429, which is a continuation of application No. 07/930,469, Aug. 20, 1992, Pat. No. 5,317,819, which is a continuation of application No. 07/239,667, Sep. 2, 1988, abandoned, which is a continuation of application No. 07/492,360, Mar. 9, 1990, Pat. No. 4,989,349, which is a continuation of application No. 07/219,387, Jul. 15, 1988, abandoned.

[51] **Int. Cl.**<sup>7</sup> ..... **A43B 13/14**

[52] **U.S. Cl.** ..... **36/25 R; 36/30 R; 36/31; 36/88; 36/114**

[58] **Field of Search** ..... 36/25 R, 114, 36/32 R, 88, 89, 14, 15, 11, 92, 93, 30 R, 91, 113, 115, 127, 129, 140, 144, 143

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

288,127	11/1883	Shepard .	
532,429	1/1895	Rogers .	
1,283,335	10/1918	Shillcock .	
1,735,986	11/1929	Wray .	
1,853,034	4/1932	Bradley .....	36/14
2,147,197	2/1939	Glidden .	
2,328,242	8/1943	Witherill .	
2,627,676	2/1953	Hack .	
2,718,715	9/1955	Spilman .....	36/12
3,100,354	8/1963	Lombard et al. .	
3,308,560	3/1967	Jones .	
3,997,984	12/1976	Hayward .	
4,003,145	1/1977	Liebscher et al. ....	36/117 PW

**FOREIGN PATENT DOCUMENTS**



1176458	10/1984	Canada .	
1004472	11/1951	France .....	36/59 C
2 006 270	10/1971	France .	
1 287 477	1/1969	Germany .	
1290844	3/1969	Germany .	
1685260	10/1971	Germany .	
3317462 A1	10/1983	Germany .	
23257	3/1995	Germany .	
16143	of 1892	United Kingdom .	
807305	1/1959	United Kingdom .	
2136670	9/1984	United Kingdom .	
91/10377	7/1991	WIPO .	

*Primary Examiner*—David T. Fidei  
*Attorney, Agent, or Firm*—Finnegan, Henderson, Farabow, Garrett & Dunner, L.L.P.

[57] **ABSTRACT**


A construction for a shoe, particularly an athletic shoe such as a running shoe, includes a sole that conforms to the natural shape of the foot, particularly the sides, and that has a constant thickness in frontal plane cross sections. The thickness of the shoe sole side contour equals and therefore varies exactly as the thickness of the load-bearing sole portion varies due to heel lift, for example. Thus, the outer contour of the edge portion of the sole has at least a portion which lies along a theoretically ideal stability plane for providing natural stability and efficient motion of the shoe and foot particularly in an inverted and everted mode.

**29 Claims, 19 Drawing Sheets**




U.S. PATENT DOCUMENTS					
			4,624,061	11/1986	Wezel et al. .
			4,676,010	6/1987	Cheskin .
4,262,433	4/1981	Hagg et al. .	4,715,133	12/1987	Hartjes et al. .
4,272,858	6/1981	Hlustik ..... 36/11	4,727,660	3/1988	Bernhard .
4,308,671	1/1982	Bretschneider .	4,827,631	5/1989	Thornton .
4,322,895	4/1982	Hockerson .	4,837,949	6/1989	DuFour .
4,335,529	6/1982	Badalamenti .	4,854,057	8/1989	Misevich et al. .
4,348,821	9/1982	Daswick .	4,858,340	8/1989	Pasternak .
4,361,971	12/1982	Bowerman .	4,866,861	9/1989	Noone .
4,366,634	1/1983	Giese et al. .	4,890,398	1/1990	Thomasson .
4,398,357	8/1983	Batra ..... 36/31	4,906,502	3/1990	Rudy .
4,449,306	5/1984	Cavanaugh .	4,989,349	2/1991	Ellis, III ..... 36/25 R
4,455,767	6/1984	Bergmans .	5,024,007	6/1991	DuFour .
4,506,462	3/1985	Cavanagh .	5,025,573	6/1991	Giese et al. .... 36/31
4,542,598	9/1985	Misevich et al. .	5,052,130	10/1991	Barry et al. .
4,557,059	12/1985	Misevich et al. .	5,224,280	7/1993	Preman et al. .
4,559,723	12/1985	Hamy et al. .	5,237,758	8/1993	Zachman .
4,577,417	3/1986	Cole .	5,317,819	6/1994	Ellis, III ..... 36/25 R
4,578,882	4/1986	Talarico, II .	5,543,194	8/1996	Rudy .
4,580,359	4/1986	Kurrash et al. .			


**FIG. 1**  
(PRIOR ART)



**FIG. 2A**  
(PRIOR ART)




**FIG. 2**



**FIG. 2B**  
(PRIOR ART)

**FIG. 2C**



**FIG. 2D**




FIG. 3





FIG. 4D




FIG. 5

FIG. 5A




FIG. 5B




FIG. 6




FIG. 7A




FIG. 7

FIG. 7D

FIG. 7B




FIG. 7C





FIG. 8




FIG. 9




FIG. 9B




FIG. 9C




FIG. 10




FIG. 10A

FIG. 10B




FIG. 10B



FIG. II




FIG. IIB



FIG. IIC




FIG. IID




FIG. IIE




FIG. 12A




FIG. 12

FIG. 12B




FIG. 12C




FIG. 12D




FIG. 13

FIG. 13A




FIG. 13B




FIG. 13C




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

FIG. 18A




FIG. 18B




FIG. 19A




FIG. 19

FIG. 19F




FIG. 19B




FIG. 19C




FIG. 19D





FIG. 19E








FIG. 22

FIG. 22A




FIG. 22B




FIG. 23




FIG. 24




FIG. 25




FIG. 25B




FIG. 26




FIG. 27




FIG. 28A




FIG. 28




FIG. 28B






FIG. 28C





**FIG. 29**

## SHOE WITH NATURALLY CONTOURED SOLE

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of application Ser. No. 08/162,962 filed Dec. 8, 1993, now U.S. Pat. No. 5,544,429 which is a continuation of Ser. No. 07/930,469 filed Aug. 20, 1992, now U.S. Pat. No. 5,317,819 issued Jun. 7, 1994 which is a continuation of Ser. No. 07/239,667 filed Sep. 2, 1988, now abandoned and application Ser. No. 07/492,360, filed Mar. 9, 1990, now U.S. Pat. No. 4,989,349 issued Feb. 5, 1991 which is a continuation of Ser. No. 07/219,387, filed Jul. 15, 1988, now abandoned.

### BACKGROUND OF THE INVENTION

This invention relates to a shoe, such as a street shoe, athletic shoe, and especially a running shoe with a contoured sole. More particularly, this invention relates to a novel contoured sole design for a running shoe which improves the inherent stability and efficient motion of the shod foot in extreme exercise. Still more particularly, this invention relates to a running shoe wherein the shoe sole conforms to the natural shape of the foot, particularly the sides, and has a constant thickness in frontal plane cross sections, permitting the foot to react naturally with the ground as it would if the foot were bare, while continuing to protect and cushion the foot.

By way of introduction, barefoot populations universally have a very low incidence of running "overuse" injuries, despite very high activity levels. In contrast, such injuries are very common in shoe shod populations, even for activity levels well below "overuse". Thus, it is a continuing problem with a shod population to reduce or eliminate such injuries and to improve the cushioning and protection for the foot. It is primarily to an understanding of the reasons for such problems and to proposing a novel solution according to the invention to which this improved shoe is directed.

A wide variety of designs are available for running shoes which are intended to provide stability, but which lead to a constraint in the natural efficient motion of the foot and ankle. However, such designs which can accommodate free, flexible motion in contrast create a lack of control or stability. A popular existing shoe design incorporates an inverted, outwardly-flared shoe sole wherein the ground engaging surface is wider than the heel engaging portion. However, such shoes are unstable in extreme situations because the shoe sole, when inverted or on edge, immediately becomes supported only by the sharp bottom sole edge where the entire weight of the body, multiplied by a factor of approximately three at running peak, is concentrated. Since an unnatural lever arm and force moment are created under such conditions, the foot and ankle are destabilized and, in the extreme, beyond a certain point of rotation about the pivot point of the shoe sole edge, forceably cause ankle strain. In contrast, the unshod foot is always in stable equilibrium without a comparable lever arm or force moment and, at its maximum range of inversion motion, about 200, the base of support on the barefoot heel actually broadens substantially as the calcaneal tuberosity contacts the ground. This is in contrast to the conventionally available shoe sole bottom which maintains a sharp, unstable edge.

It is thus an overall objective of this invention to provide a novel shoe design which approximates the barefoot. It has been discovered, by investigating the most extreme range of

ankle motion to near the point of ankle sprain, that the abnormal motion of an inversion ankle sprain, which is a tilting to the outside or an outward rotation of the foot, is accurately simulated while stationary. With this observation, it can be seen that the extreme range stability of the conventionally shod foot is distinctly inferior to the barefoot and that the shoe itself creates a gross instability which would otherwise not exist.

Even more important, a normal barefoot running motion, which approximately includes a 7° inversion and a 7° eversion motion, does not occur with shod feet, where a 30° inversion and eversion is common. Such a normal barefoot motion is geometrically unattainable because the average running shoe heel is approximately 60% larger than the width of the human heel. As a result, the shoe heel and the human heel cannot pivot together in a natural manner; rather, the human heel has to pivot within the shoe but is resisted from doing so by the shoe heel counter, motion control devices, and the lacing and binding of the shoe upper, as well as various types of anatomical supports interior to the shoe.

Thus, it is an overall objective to provide an improved shoe design which is not based on the inherent contradiction present in current shoe designs which make the goals of stability and efficient natural motion incompatible and even mutually exclusive. It is another overall object of the invention to provide a new contour design which simulates the natural barefoot motion in running and thus avoids the inherent contradictions in current designs.

It is another objective of this invention to provide a running shoe which overcomes the problem of the prior art.

It is another objective of this invention to provide a shoe wherein the outer extent of the flat portion of the sole of the shoe includes all of the support structures of the foot but which extends no further than the outer edge of the flat portion of the shoe sole so that the transverse or horizontal plane outline of the top of the flat portion of the shoe sole coincides as nearly as possible with the loadbearing portion of the foot sole.

It is another objective of the invention to provide a shoe having a sole which includes a side contoured like the natural form of the side or edge of the human foot and conforming to it.

It is another objective of this invention to provide a novel shoe structure in which the contoured sole includes a shoe sole thickness that is precisely constant in frontal plane cross sections, and therefore biomechanically neutral, even if the shoe sole is tilted to either side, or forward or backward.

It is another objective of this invention to provide a shoe having a sole fully contoured like and conforming to the natural form of the non-load-bearing human foot and deforming under load by flattening just as the foot does.

It is still another objective of this invention to provide a new stable shoe design wherein the heel lift or wedge increases in the sagittal plane the thickness of the shoe sole or toe taper decrease therewith so that the sides of the shoe sole which naturally conform to the sides of the foot also increase or decrease by exactly the same amount, so that the thickness of the shoe sole in a frontal planar cross section is always constant.

These and other objectives of the invention will become apparent from a detailed description of the invention which follows taken in conjunction with the accompanying drawings.

## BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

FIG. 1 is a perspective view of a typical running shoe known to the prior art to which the invention is applicable;

FIG. 2A illustrates the obstructed natural motion of the shoe heel in frontal planar cross section rotating inwardly or in FIG. 2B, outwardly with the shoe sole having a flared bottom in a conventional prior art design such as in FIG. 1; FIG. 2C illustrates the efficient motion of a narrow rectangular shoe sole design inwardly and, in FIG. 2D, outwardly;

FIG. 3 is a frontal plane cross section showing a shoe sole of uniform thickness that conforms to the natural shape of the human foot, the novel shoe design according to the invention;

FIG. 4A illustrates a load-bearing naturally contoured stability side component of a shoe sole; FIG. 4B illustrates the load-bearing flat component thereof; FIG. 4C illustrates the flat and contoured components together and FIG. 4D is as well as a preferred horizontal periphery of the flat load-bearing portion of the shoe sole when using the sole of the invention;

FIG. 5A is diagrammatic sketch showing the novel contoured side sole design according to the invention with one heel lift and, in FIG. 5B, with another heel lift;

FIG. 6 is a side view of the novel stable contoured shoe according to the invention showing the contoured side design;

FIG. 7A is a cross-sectional view of the forefoot portion taken along lines 7A of FIGS. 6 or 7D; FIG. 7B is a view taken along lines 7B of FIGS. 6 and 7D; and FIG. 7C is a cross-sectional view taken along the heel along lines 7C in FIGS. 6 and 7D; and FIG. 7D is a top view of the shoe sole of FIG. 6;

FIG. 8 is a drawn comparison between a conventional flared sole shoe of the prior art and the contoured shoe design according to the invention;

FIG. 9A is the extremely stable condition for the novel shoe sole according to the invention in its neutral position; FIG. 9B is a similar view in one extreme situation; and FIG. 9C in a more extreme situation;

FIG. 10A is a composite side cross-sectional view of the naturally contoured sole side showing how the sole maintains a constant distance from the ground during rotation of the shoe edge; FIG. 10B is a similar view of the prior art sole;

FIGS. 11A, 11B, 11C, 11D, 11E and 12D are a plurality of side sagittal plane cross-sectional views showing examples of conventional sole thickness variations to which the invention can be applied;

FIG. 12A, 12B, 12C and 12D are frontal plane cross-sectional views of the shoe sole according to the invention showing a theoretically ideal stability plane and truncations of the sole side contour to reduce shoe bulk;

FIGS. 13A, 13B and 13C shows the contoured sole design according to the invention when applied to various tread and cleat patterns;

FIG. 14 illustrates, in a rear view, an application of the sole according to the invention to a shoe to provide an aesthetically pleasing and functionally effective design;

FIG. 15 shows a fully contoured shoe sole design that follows the natural contour of the bottom of the foot as well as the sides;

FIG. 16 is a diagrammatic side cross-sectional view of static forces acting on the ankle joint and its position relative

to the shoe sole according to the invention during normal and extreme inversion and eversion motion;

FIG. 17 is a diagrammatic view of a plurality of moment curves of the center of gravity for various degrees of inversion for the shoe sole according to the invention, and contrasted to the motions shown in FIG. 2;

in FIGS. 18A and 18B, are rear diagrammatic views of a human heel, as relating to a conventional shoe sole (FIG. 18A) and to the sole of the invention (FIG. 18B);

FIG. 19A is a sectional view taken along line 19A of FIG. 19F, showing line 26, after "arch;" add the naturally contoured sides design extended to the other natural contours underneath the loadbearing foot such as the main longitudinal arch; FIG. 19B is likewise taken along line 19B of FIG. 19F; FIG. 19C is taken along line 19C of FIG. 19F; FIG. 19D is taken along line 19D of FIG. 19F; and FIG. 19E is a sagittal section taken along line 19F; FIG. 19F is a top plan view of a sole of the invention;

FIG. 20A is a sectional view taken along line 20A of FIG. 21, showing the fully contoured shoe sole design extended to the bottom of the entire non-load-bearing foot; FIG. 20B is taken on line 20B, FIG. 20C is on line 20C, FIG. 20D on line 20D, all in FIG. 21; FIGS. 20D and 20E is a sagittal section taken on line 20E of FIG. 21;

FIG. 21 shows the fully contoured shoe sole design abbreviated along the sides to only essential structural support and propulsion element or bulges;

FIG. 22A and 22B illustrates the application of the invention to provide a street shoe with a correctly contoured sole according to the invention and side edges perpendicular to the ground, as is typical of a street shoe; and FIG. 22B is a similar view of another street shoe;

FIG. 23 shows a method of establishing the theoretically ideal stability plane using a perpendicular to a tangent method;

FIG. 24 shows a circle radius method of establishing the theoretically ideal stability plane.

FIG. 25A illustrates an alternate embodiment of the invention wherein the sole structure deforms in use to follow a theoretically ideal stability plane according to the invention during deformation; FIG. 25B is a similar view of another embodiment of the invention;

FIG. 26 shows an embodiment wherein the contour of the sole according to the invention is approximated by a plurality of line segments;

FIG. 27 illustrates an embodiment wherein the stability sides are determined geometrically as a section of a ring;

FIG. 28A shows a shoe sole design that allows for unobstructed natural eversion/inversion motion by providing torsional flexibility in the instep area of the shoe sole; and FIGS. 28B and 28C is a similar view of another embodiment; and

FIG. 29 illustrates a process for measuring the contoured shoe sole sides of the applicant's invention.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A perspective view of an athletic shoe, such as a typical running shoe, according to the prior art, is shown in FIG. 1 wherein a running shoe 20 includes an upper portion 21 and a sole 22. Typically, such a sole includes a truncated outwardly flared construction of the type best seen in FIG. 2 wherein the lower portion 22a of the sole heel is significantly wider than the upper portion 22b where the sole 22

joins the upper **21**. A number of alternative sole designs are known to the art, including the design shown in U.S. Pat. No. 4,449,306 to Cavanagh wherein an outer portion of the sole of the running shoe includes a rounded portion having a radius of curvature of about 20 mm. The rounded portion lies along approximately the rear-half of the length of the outer side of the mid-sole and heel edge areas wherein the remaining border area is provided with a conventional flaring with the exception of a transition zone. The U.S. Patent to Misevich, No. 4,557,059 also shows an athletic shoe having a contoured sole bottom in the region of the first foot strike, in a shoe which otherwise uses an inverted flared sole.

In such prior art designs, and especially in athletic and in running shoes, the typical design attempts to achieve stability by flaring the heel as shown in FIGS. **2A** and **2B** to a width of, for example, 3 to 3½ inches on the bottom outer sole **22a** of the average male shoe size (10D). On the other hand, the width of the corresponding human heel foot print, housed in the upper **21**, is only about 2.25 in. for the average foot. Therefore, a mismatch occurs in that the heel is locked by the design into a firm shoe heel counter which supports the human heel by holding it tightly and which may also be re-enforced by motion control devices to stabilize the heel. Thus, for natural motion as is shown in FIGS. **2A** and **2B**, the human heel would normally move in a normal range of motion of approximately 15°, but as shown in FIGS. **2A** and **2B** the human heel cannot pivot except within the shoe and is resisted by the shoe. Thus, FIG. **2A** illustrates the impossibility of pivoting about the center edge of the human heel as would be conventional for barefoot support about a point **23** defined by a line **23a** perpendicular to the heel and intersecting the bottom edge of upper **21** at a point **24**. The lever arm force moment of the flared sole is at a maximum at 0° and only slightly less at a normal 7° inversion or eversion and thus strongly resists such a natural motion as is illustrated in FIGS. **2A** and **2B**. In FIG. **2A**, the outer edge of the heel must compress to accommodate such motion. FIG. **2B** illustrates that normal natural motion of the shoe is inefficient in that the center of gravity of the shoe, and the shod foot, is forced upperwardly, as discussed later in connection with FIG. **17**.

A narrow rectangular shoe sole design of heel width approximating human heel width is also known and is shown in FIGS. **2C** and **2D**. It appears to be more efficient than the conventional flared sole shown in FIGS. **2A** and **2B**. Since the shoe sole width is the same as human sole width, the shoe can pivot naturally with the normal 7° inversion/eversion motion of the running barefoot. In such a design, the lever arm length and the vertical motion of the center of gravity are approximately half that of the flared sole at a normal 7° inversion/eversion running motion. However, the narrow, human heel width rectangular shoe design is extremely unstable and therefore prone to ankle sprain, so that it has not been well received. Thus, neither of these wide or narrow designs is satisfactory.

FIG. **3** shows in a frontal plane cross section at the heel (center of ankle joint) the general concept of the applicant's design: a shoe sole **28** that conforms to the natural shape of the human foot **27** and that has a constant thickness (s) in frontal plane cross sections. The surface **29** of the bottom and sides of the foot **27** should correspond exactly to the upper surface **30** of the shoe sole **28**. The shoe sole thickness is defined as the shortest distance (s) between any point on the upper surface **30** of the shoe sole **28** and the lower surface **31** (FIGS. **23** and **24** will discuss measurement methods more fully). In effect, the applicant's general con-

cept is a shoe sole **28** that wraps around and conforms to the natural contours of the foot **27** as if the shoe sole **28** were made of a theoretical single flat sheet of shoe sole material of uniform thickness, wrapped around the foot with no distortion or deformation of that sheet as it is bent to the foot's contours. To overcome real world deformation problems associated with such bending- or wrapping around contours, actual construction of the shoe sole contours of uniform thickness will preferably involve the use of multiple sheet lamination or injection molding techniques.

FIGS. **4A**, **4B**, and **4C** illustrate in frontal plane cross section a significant element of the applicant's shoe design in its use of naturally contoured stabilizing sides **28a** at the outer edge of a shoe sole **28b** illustrated generally at the reference numeral **28**. It is thus a main feature of the applicant's invention to eliminate the unnatural sharp bottom edge, especially of flared shoes, in favor of a naturally contoured shoe sole outside **31** as shown in FIG. **3**. The side or inner edge **30a** of the shoe sole stability side **28a** is contoured like the natural form on the side or edge of the human foot, as is the outside or outer edge **31a** of the shoe sole stability side **28a** to follow a theoretically ideal stability plane. According to the invention, the thickness (s) of the shoe sole **28** is maintained exactly constant, even if the shoe sole is tilted to either side, or forward or backward. Thus, the naturally contoured stabilizing sides **28a**, according to the applicant's invention, are defined as the same as the thickness **33** of the shoe sole **28** so that, in cross section, the shoe sole comprises a stable shoe sole **28** having at its outer edge naturally contoured stabilizing sides **28a** with a surface **31a** representing a portion of a theoretically ideal stability plane and described by naturally contoured sides equal to the thickness (s) of the sole **28**. The top of the shoe sole **30b** coincides with the shoe wearer's load-bearing footprint, since in the case shown the shape of the foot is assumed to be load-bearing and therefore flat along the bottom. A top edge **32** of the naturally contoured stability side **28a** can be located at any point along the contoured side of the foot **29**, while the inner edge **33** of the naturally contoured side **28a** coincides with the perpendicular sides **34** of the load-bearing shoe sole **28b**. In practice, the shoe sole **28** is preferably integrally formed from the portions **28b** and **28a**. Thus, the theoretically ideal stability plane includes the contours **31a** merging into the lower surface **31b** of the sole **28**. Preferably, the peripheral extent **36** of the load-bearing portion of the sole **28b** of the shoe includes all of the support structures of the foot but extends no further than the outer edge of the foot sole **37** as defined by a loadbearing footprint, as shown in FIG. **4D**, which is a top view of the upper shoe sole surface **30b**. FIG. **4D** thus illustrates a foot outline at numeral **37** and a recommended sole outline **36** relative thereto. Thus, a horizontal plane outline of the top of the load-bearing portion of the shoe sole, therefore exclusive of contoured stability sides, should, preferably, coincide as nearly as practicable with the load-bearing portion of the foot sole with which it comes into contact. Such a horizontal outline, as best seen in FIGS. **4D** and **7D**, should remain uniform throughout the entire thickness of the shoe sole eliminating negative or positive sole flare so that the sides are exactly perpendicular to the horizontal plane as shown in FIG. **4B**. Preferably, the density of the shoe sole material is uniform.

Another significant feature of the applicant's invention is illustrated diagrammatically in FIG. **5**. Preferably, as the heel lift or wedge **38** of thickness (s1) increases the total thickness (s+s1) of the combined midsole and outsole **39** of thickness (s) in an aft direction of the shoe, the naturally



contoured sides **28a** increase in thickness exactly the same amount according to the principles discussed in connection with FIG. 4. Thus, according to the applicant's design, the thickness of the inner edge **33** of the naturally contoured side is always equal to the constant thickness (s) of the load-bearing shoe sole **28b** in the frontal cross-sectional plane.

As shown in FIG. 5B, for a shoe that follows a more conventional horizontal plane outline, the sole can be improved significantly according to the applicant's invention by the addition of a naturally contoured side **28a** which correspondingly varies with the thickness of the shoe sole and changes in the frontal plane according to the shoe heel lift. Thus, as illustrated in FIG. 5B, the thickness of the naturally contoured side **28a** is equal to the thickness (s+s1) of the shoe sole **28** which is thicker than the shoe sole (s) shown in FIG. 5A by an amount equivalent to the heel lift (s1). In the generalized case, the thickness (s) of the contoured side is thus always equal to the thickness (s) of the shoe sole.

FIG. 6 illustrates a side cross-sectional view of a shoe to which the invention has been applied and is also shown in a top plane view in FIG. 7. Thus, FIGS. 7A, 7B and 7C represent frontal plane cross-sections taken along the forefoot, at the base of the fifth metatarsal, and at the heel, thus illustrating that the shoe sole thickness is constant at each frontal plane cross-section, even though that thickness varies from front to back, due to the heel lift **38** as shown in FIG. 6, and that the thickness of the naturally contoured sides is equal to the shoe sole thickness in each FIG. 7A-7C cross section. Moreover, in FIG. 7D, a horizontal plane overview of the left foot, it can be seen that the contour of the sole follows the preferred principle in matching, as nearly as practical, the load-bearing sole print shown in FIG. 4D.

FIG. 8 thus contrasts in frontal plane cross section the conventional flared sole **22** shown in phantom outline and illustrated in FIG. 2 with the contoured shoe sole **28** according to the invention as shown in FIGS. 3-7.

FIG. 9 is suitable for analyzing the shoe sole design according to the applicant's invention by contrasting the neutral situation shown in FIG. 9A with the extreme situations shown in FIGS. 9B and 9C. Unlike the sharp sole edge of a conventional shoe as shown in FIG. 2, the effect of the applicant's invention having a naturally contoured side **28a** is totally neutral allowing the shod foot to react naturally with the ground **43**, in either an inversion or eversion mode. This occurs in part because of the unvarying thickness along the shoe sole edge which keeps the foot sole equidistant from the ground in a preferred case. Moreover, because the shape of the edge **31a** of the shoe contoured side **28a** is exactly like that of the edge of the foot, the shoe is enabled to react naturally with the ground in a manner as closely as possible simulating the foot. Thus, in the neutral position shown in FIG. 9, any point **40** on the surface of the shoe sole **30b** closest to ground lies at a distance (s) from the ground surface **39**. That distance (s) remains constant even for extreme situations as seen in FIGS. 9B and 9C.

A main point of the applicant's invention, as is illustrated in FIGS. 9B and 9C, is that the design shown is stable in an extremis situation. The ideal plane of stability where the stability plane is defined as sole thickness which is constant under all load-bearing points of the foot sole for any amount from 0° to 90° rotation of the sole to either side or front and back. In other words, as shown in FIG. 9, if the shoe is tilted from 0° to 90° to either side or from 0° to 90° forward or backward representing a 0° to 90° foot dorsiflexion or 0° to

90° plantarflexion, the foot will remain stable because the sole thickness (s) between the foot and the ground always remain constant because of the exactly contoured quadrant sides. By remaining a constant distance from the ground, the stable shoe allows the foot to react to the ground as if the foot were bare while allowing the foot to be protected and cushioned by the shoe. In its preferred embodiment, the new naturally contoured sides will effectively position and hold the foot onto the load-bearing foot print section of the shoe sole, reducing the need for heel counters and other motion control devices.

FIG. 10A illustrates how the inner edge **30a** of the naturally contoured sole side **28a** is maintained at a constant distance (s) from the ground through various degrees of rotation of the edge **31a** of the shoe sole such as is shown in FIG. 9. FIG. 10B shows how a conventional shoe sole pivots around its lower edge **42**, which is its center of rotation, instead of around the upper edge **40**, which, as a result, is not maintained at constant distance (s) from the ground, as with the invention, but is lowered to 0.7 (s) at 45° rotation and to zero at 90° rotation.

FIG. 11 shows typical conventional sagittal plane shoe sole thickness variations, such as heel lifts or wedges **38**, or toe taper **38a**, or full sole taper **38b**, in FIGS. 11A-11E and how the naturally contoured sides **28a** equal and therefore vary with those varying thicknesses as discussed in connection with FIG. 5.

FIG. 12 illustrates an embodiment of the invention which utilizes varying portions of the theoretically ideal stability plane **51** in the naturally contoured sides **28a** in order to reduce the weight and bulk of the sole, while accepting a sacrifice in some stability of the shoe. Thus, FIG. 12A illustrates the preferred embodiment as described above in connection with FIG. 5 wherein the outer edge **31a** of the naturally contoured sides **28a** follows a theoretically ideal stability plane **51**. As in FIGS. 3 and 4, the contoured surfaces **31a**, and the lower surface of the sole **31b** lie along the theoretically ideal stability plane **51**. The theoretically ideal stability plane **51** is defined as the plane of the surface of the bottom of the shoe sole **31**, wherein the shoe sole conforms to the natural shape of the foot, particularly the sides, and has a constant thickness in frontal plane cross sections. As shown in FIG. 12B, an engineering trade off results in an abbreviation within the theoretically ideal stability plane **51** by forming a naturally contoured side surface **53a** approximating the natural contour of the foot (or more geometrically regular, which is less preferred) at an angle relative to the upper plane of the shoe sole **28** so that only a smaller portion of the contoured side **28a** defined by the constant thickness lying along the surface **31a** is coplanar with the theoretically ideal stability plane **51**. FIGS. 12C and 12D show similar embodiments wherein each engineering trade-off shown results in progressively smaller portions of contoured side **28a**, which lies along the theoretically ideal stability plane **51**. The portion of the surface **31a** merges into the upper side surface **53a** of the naturally contoured side.

The embodiment of FIG. 12 may be desirable for portions of the shoe sole which are less frequently used so that the additional part of the side is used less frequently. For example, a shoe may typically roll out laterally, in an inversion model to about 20° on the order of 100 times for each single time it rolls out to 40°. For a basketball shoe, shown in FIG. 12B, the extra stability is needed. Yet, the added shoe weight to cover that infrequently experienced range of motion is about equivalent to covering the frequently encountered range. Since, in a racing shoe this

weight might not be desirable, an engineering trade-off of the type shown in FIG. 12D is possible. A typical running/jogging shoe is shown in FIG. 12C. The range of possible variations is limitless.

FIG. 13 shows the theoretically ideal stability plane 51 in defining embodiments of the shoe sole having differing tread or cleat patterns. Thus, FIG. 13 illustrates that the invention is applicable to shoe soles having conventional bottom treads. Accordingly, FIG. 13A is similar to FIG. 12B further including a tread portion 60, while FIG. 13B is also similar to FIG. 12B wherein the sole includes a cleated portion 61. The surface 63 to which the cleat bases are affixed should preferably be on the same plane and parallel the theoretically ideal stability plane 51, since in soft ground that surface rather than the cleats become loadbearing. The embodiment in FIG. 13C is similar to FIG. 12C showing still an alternative tread construction 62. In each case, the load-bearing outer surface of the tread or cleat pattern 60-62 lies along the theoretically ideal stability plane 51.

FIG. 14 shows, in a rear cross sectional view, the application of the invention to a shoe to produce an aesthetically pleasing and functionally effective design. Thus, a practical design of a shoe incorporating the invention is feasible, even when applied to shoes incorporating heel lifts 38 and a combined midsole and outsole 93. Thus, use of a sole surface and sole outer contour which track the theoretically ideal stability plane does not detract from the commercial appeal of shoes incorporating the invention.

FIG. 15 shows a fully contoured shoe sole design that follows the natural contour of all of the foot, the bottom as well as the sides. The fully contoured shoe sole assumes that the resulting slightly rounded bottom when unloaded will deform under load and flatten just as the human foot bottom is slightly rounded unloaded but flattens under load; therefore, shoe sole material must be of such composition as to allow the natural deformation following that of the foot. The design applies particularly to the heel, but to the rest of the shoe sole as well. By providing the closest match to the natural shape of the foot, the fully contoured design allows the foot to function as naturally as possible. Under load, FIG. 15 would deform by flattening to look essentially like FIG. 14. Seen in this light, the naturally contoured side design in FIG. 14 is a more conventional, conservative design that is a special case of the more general fully contoured design in FIG. 15, which is the closest to the natural form of the foot, but the least conventional. The amount of deformation flattening used in the FIG. 14 design, which obviously varies under different loads, is not an essential element of the applicant's invention.

FIGS. 14 and 15 both show in frontal plane cross section the essential concept underlying this invention, the theoretically ideal stability plane, which is also theoretically ideal for efficient natural motion of all kinds, including running, jogging or walking. FIG. 15 shows the most general case of the invention, the fully contoured design, which conforms to the natural shape of the unloaded foot. For any given individual, the theoretically ideal stability plane 31 is determined, first, by the desired shoe sole thickness (s) in a frontal plane cross section, and, second, by the natural shape of the individuals foot surface 29.

For the special case shown in FIG. 14, the theoretically ideal stability plane for any particular individual (or size average of individuals) is determined, first, by the given frontal plane cross section shoe sole thickness (s); second, by the natural shape of the individual's foot; and, third, by the frontal plane cross section width of the individuals

load-bearing footprint 30b, which is defined as the upper surface of the shoe sole that is in physical contact with and supports the human foot sole, as-shown in FIG. 4.

The theoretically ideal stability plane for the special case is composed conceptionally of two parts. Shown in FIGS. 14 and 4 the first part is a line segment 31b of equal length and parallel to 30b at a constant distance (s) equal to shoe sole thickness. This corresponds to a conventional shoe sole directly underneath the human foot, and also corresponds to the flattened portion of the bottom of the load-bearing foot sole 28b. The second part is the naturally contoured stability side outer edge 31a located at each side of the first part, line segment 31b. Each point on the contoured side outer edge 31a is located at a distance which is exactly shoe sole thickness (s) from the closest point on the contoured side inner edge 30a.

In summary, the theoretically ideal stability plane is the essence of this invention because it is used to determine a geometrically precise bottom contour of the shoe sole based on a top contour that conforms to the contour of the foot. This invention specifically claims the exactly determined geometric relationship just described. It can be stated unequivocally that any shoe sole contour, even of similar contour, that exceeds the theoretically ideal stability plane will restrict natural foot motion, while any less than that plane will degrade natural stability, in direct proportion to the amount of the deviation.

FIG. 16 illustrates in a curve 70 the range of side to side inversion/eversion motion of the ankle center of gravity 71 from the shoe according to the invention shown in frontal plane cross section at the ankle. Thus, in a static case where the center of gravity 71 lies at approximately the mid-point of the sole, and assuming that the shoe inverts or everts from 0° to 20° to 40°, as shown in progressions 16a, 16b and 16c, the locus of points of motion for the center of gravity thus defines the curve 70 wherein the center of gravity 71 maintains a steady level motion with no vertical component through 40° of inversion or eversion. For the embodiment shown, the shoe sole stability equilibrium point is at 28° (at point 74) and in no case is there a pivoting edge to define a rotation point as in the case of FIG. 2. The inherently superior side to side stability of the design provides pronation control (or eversion), as well as lateral (or inversion) control. In marked contrast to conventional shoe sole designs, the applicant's shoe design creates virtually no abnormal torque to resist natural inversion/eversion motion or to destabilize the ankle joint.

FIG. 17 thus compares the range of motion of the center of gravity for invention, as shown in curve 75, in comparison to curve 80 for the conventional wide heel flare and a curve 82 for a narrow rectangle the width of a human heel. Since the shoe stability limit is 28° in the inverted mode, the shoe sole is stable at the 20° approximate barefoot inversion limit. That factor, and the broad base of support rather than the sharp bottom edge of the prior art, make the contour design stable even in the most extreme case as shown in FIGS. 16 and permit the inherent stability of the barefoot to dominate without interference, unlike existing designs, by providing constant, unvarying shoe sole thickness in frontal plane cross sections. The stability superiority of the contour side design is thus clear when observing how much flatter its center of gravity curve 75 is than in existing popular wide flare design 80. The curve demonstrates that the contour side design has significantly more efficient natural 7° inversion/eversion motion than the narrow rectangle design the width of a human heel, and very much more efficient than the conventional wide flare design; at the same time, the contour

side design is more stable in extremis than either conventional design because of the absence of destabilizing torque.

FIG. 18A illustrates, in a pictorial fashion, a comparison of a cross section at the ankle joint of a conventional shoe with a cross section of a shoe according to the invention when engaging a heel. As seen in FIG. 18A, when the heel of the foot 27 of the wearer engages an upper surface of the shoe sole 22, the shape of the foot heel and the shoe sole is such that the shoe sole 22 conforms to the contour of the ground 43 and not to the contour of the sides of the foot 27. As a result, the shoe sole 22 cannot follow the natural  $7^\circ$  inversion/eversion motion of the foot, and that normal motion is resisted by the shoe upper 21, especially when strongly reinforced by firm heel counters and motion control devices. This interference with natural motion represents the fundamental misconception of the currently available designs. That misconception on which existing shoe designs are based is that, while shoe uppers are considered as a part of the foot and conform to the shape of the foot, the shoe sole is functionally conceived of as a part of the ground and is therefore shaped like the ground, rather than the foot.

In contrast, the new design, as illustrated in FIG. 18B, illustrates a correct conception of the shoe sole 28 as a part of the foot and an extension of the foot, with shoe sole sides contoured exactly like those of the foot, and with the frontal plane thickness of the shoe sole between the foot and the ground always the same and therefore completely neutral to the natural motion of the foot. With the correct basic conception, as described in connection with this invention, the shoe can move naturally with the foot, instead of restraining it, so both natural stability and natural efficient motion coexist in the same shoe, with no inherent contradiction in design goals.

Thus, the contoured shoe design of the invention brings together in one shoe design the cushioning and protection typical of modern shoes, with the freedom from injury and functional efficiency, meaning speed, and/or endurance, typical of barefoot stability and natural freedom of motion. Significant speed and endurance improvements are anticipated, based on both improved efficiency and on the ability of a user to train harder without injury.

These figures also illustrate that the shoe heel cannot pivot  $\pm 7$  degrees with the prior art shoe of FIG. 18A. In contrast the shoe heel in the embodiment of FIG. 18B pivots with the natural motion of the foot heel.

FIGS. 19A–D illustrate, in frontal plane cross sections, the naturally contoured sides design extended to the other natural contours underneath the load-bearing foot, such as the main longitudinal arch, the metatarsal (or forefoot) arch, and the ridge between the heads of the metatarsals (forefoot) and the heads of the distal phalanges (toes). As shown, the shoe sole thickness remains constant as the contour of the shoe sole follows that of the sides and bottom of the load-bearing foot. FIG. 19E shows a sagittal plane cross section of the shoe sole conforming to the contour of the bottom of the load-bearing foot, with thickness varying according to the heel lift 38. FIG. 19F shows a horizontal plane top view of the left foot that shows the areas 85 of the shoe sole that corresponds to the flattened portions of the foot sole that are in contact with the ground when loadbearing. Contour lines 86 and 87 show approximately the relative height of the shoe sole contours above the flattened load-bearing areas 85 but within roughly the peripheral extent 36 of the load-bearing portion of sole 28b shown in FIG. 4. A horizontal plane bottom view (not shown) of FIG. 19F would be the exact reciprocal or converse of FIG. 19F (i.e., peaks and valleys contours would be exactly reversed).

FIGS. 20A–D show, in frontal plane cross sections, the fully contoured shoe sole design extended to the bottom of the entire non-load-bearing foot. FIG. 20E shows a sagittal plane cross section. The shoe sole contours underneath the foot are the same as FIGS. 19A–E except that there are no flattened areas corresponding to the flattened areas of the load-bearing foot. The exclusively rounded contours of the shoe sole follow those of the unloaded foot. A heel lift 38, the same as that of FIG. 19, is incorporated in this embodiment, but is not shown in FIG. 20.

FIG. 21 shows the horizontal plane top view of the left foot corresponding to the fully contoured design described in FIGS. 20A–E, but abbreviated or indented at 96a, 96b and 97a along the sides to only essential structural support and propulsion elements or convex rounded bulges as shown. Shoe sole material density can be increased in the unabbreviated essential elements to compensate for increased pressure loading there. The essential structural support elements are the convex rounded bulges at the base 95b and lateral 95c tuberosity of the calcaneus 95, the medial and lateral heads 96d and 96e of the metatarsals, and the base of the fifth metatarsal 97 in the lateral midtarsal portion of the sole. They must be supported both underneath at 95a, 96c, 97b and to the outside for stability so that the rounded bulges extend at the bottom and sides of the sole, and may be contoured upwardly at the lateral or medial sides and at the inner and outer surfaces of the sole as shown in FIGS. 20A to 20E. The essential propulsion element is the head of first distal phalange or forward medial forefoot part 98. The medial (inside) and lateral (outside) sides supporting the base of the calcaneus are shown in FIG. 21 oriented roughly along either side of the horizontal plane subtalar ankle joint axis, but can be located also more conventionally along the longitudinal axis of the shoe sole. A transverse indentation 96f is provided between the outer surface 98a of the forward medial forefoot part 98 and the outer surface 96c of the head of the metatarsal as shown in FIG. 20E. As shown in FIGS. 20A and 20B, the rear medial and lateral forefoot parts 96b and 96e have rounded bulges at their outer surfaces at 96c and 96g.—Line 19, after “reversed” insert—as shown at the downwardly convex rounded bulges 95a, 96c, 96g, 97b and 98a of the outer surface of the sole member. FIG. 21 shows that the naturally contoured stability sides need not be used except in the identified essential areas. Weight savings and flexibility improvements can be made by omitting the non-essential stability sides. Contour lines 85 through 89 show approximately the relative height of the shoe sole contours within roughly the peripheral extent 36 of the undeformed load-bearing portion of shoe sole 28b shown in FIG. 4. A horizontal plane bottom view (not shown) of FIG. 21 would be the exact reciprocal or converse of FIG. 21 (i.e., peaks and valleys contours would be exactly reversed).

FIG. 22A shows a development of street shoes with naturally contoured sole sides incorporating the features of the invention. FIG. 22A develops a theoretically ideal stability plane 51, as described above, for such a street shoe, wherein the thickness of the naturally contoured sides equal the shoe sole thickness. The resulting street shoe with a correctly contoured sole is thus shown in frontal plane heel cross section in FIG. 22A, with side edges perpendicular to the ground, as is typical. FIG. 22B shows a similar street shoe with a fully contoured design, including the bottom of the sole. Accordingly, the invention can be applied to an unconventional heel lift shoe, like a simple wedge, or to the most conventional design of a typical walking shoe with its heel separated from the forefoot by a hollow under the instep. The invention can be applied just at the shoe heel or

to the entire shoe sole. With the invention, as so applied, the stability and natural motion of any existing shoe design, except high heels or spike heels, can be significantly improved by the naturally contoured shoe sole design.

FIG. 23 shows a method of measuring shoe sole thickness to be used to construct the theoretically ideal stability plane of the naturally contoured side design. The constant shoe sole thickness of this design is measured at any point on the contoured sides along a line that, first, is perpendicular to a line tangent to that point on the surface of the naturally contoured side of the foot sole and, second, that passes through the same foot sole surface point.

FIG. 24 illustrates another approach to constructing the theoretically ideal stability plane, and one that is easier to use, the circle radius method. By that method, the pivot point (circle center) of a compass is placed at the beginning of the foot sole's natural side contour (frontal plane cross section) and roughly a 90° arc (or much less, if estimated accurately) of a circle of radius equal to (s) or shoe sole thickness is drawn describing the area farthest away from the foot sole contour. That process is repeated all along the foot sole's natural side contour at very small intervals (the smaller, the more accurate). When all the circle sections are drawn, the outer edge farthest from the foot sole contour (again, frontal plane cross section) is established at a distance of "s" and that outer edge coincides with the theoretically ideal stability plane. Both this method and that described in FIG. 23 would be used for both manual and CAD/CAM design applications.

The shoe sole according to the invention can be made by approximating the contours, as indicated in FIGS. 25A, 25B, and 26. FIG. 25A shows a frontal plane cross section of a design wherein the sole material in areas 107 is so relatively soft that it deforms easily to the contour of shoe sole 28 of the proposed invention. In the proposed approximation as seen in FIG. 25B, the heel cross section includes a sole upper surface 101 and a bottom sole edge surface 102 following when deformed an inset theoretically ideal stability plane 51. The sole edge surface 102 terminates in a laterally extending portion 103 joined to the heel of the sole 28. The laterally-extending portion 103 is made from a flexible material and structured to cause its lower surface 102 to terminate during deformation to parallel the inset theoretically ideal stability plane 51. Sole material in specific areas 107 is extremely soft to allow sufficient deformation. Thus, in a dynamic case, the outer edge contour assumes approximately the theoretically ideal stability shape described above as a result of the deformation of the portion 103. The top surface 101 similarly deforms to approximately parallel the natural contour of the foot as described by lines 30a and 30b shown in FIG. 4.

It is presently contemplated that the controlled or programmed deformation can be provided by either of two techniques. In one, the shoe sole sides, at especially the midsole, can be cut in a tapered fashion or grooved so that the bottom sole bends inwardly under pressure to the correct contour. The second uses an easily deformable material 107 in a tapered manner on the sides to deform under pressure to the correct contour. While such techniques produce stability and natural motion results which are a significant improvement over conventional designs, they are inherently inferior to contours produced by simple geometric shaping. First, the actual deformation must be produced by pressure which is unnatural and does not occur with a bare foot and second, only approximations are possible by deformation, even with sophisticated design and manufacturing techniques, given an individual's particular running gait or body weight. Thus, the deformation process is limited to a minor effort to correct the contours from surfaces approximating the ideal curve in the first instance.

The theoretically ideal stability can also be approximated by a plurality of line segments 110, such as tangents, chords, or other lines, as shown in FIG. 26. Both the upper surface of the shoe sole 28, which coincides with the side of the foot 30a, and the bottom surface 31a of the naturally contoured side can be approximated. While a single flat plane 110 approximation may correct many of the biomechanical problems occurring with existing designs, because it can provide a gross approximation of the both natural contour of the foot and the theoretically ideal stability plane 51, the single plane approximation is presently not preferred, since it is the least optimal. By increasing the number of flat planar surfaces formed, the curve more closely approximates the ideal exact design contours, as previously described. Single and double plane approximations are shown as line segments in the cross section illustrated in FIG. 26.

FIG. 27 shows a frontal plane cross section of an alternate embodiment for the invention showing stability sides component 28a that are determined in a mathematically precise manner to conform approximately to the sides of the foot. (The center or load-bearing shoe sole component 28b would be as described in FIG. 4). The component sides 28a would be a quadrant of a circle of radius (r+r<sup>1</sup>), where distance (r) must equal sole thickness (s); consequently the sub-quadrant of radius (r<sup>1</sup>) is removed from quadrant (r+r<sup>1</sup>). In geometric terms, the component side 28a is thus a quarter or other section of a ring. The center of rotation 115 of the quadrants is selected to achieve a sole upper side surface 30a that closely approximates the natural contour of the side of the human foot.

FIG. 27 provides a direct bridge to another invention by the applicant, a shoe sole design with quadrant stability sides.

FIG. 28 shows a shoe sole design that allows for unobstructed natural inversion/eversion motion of the calcaneus by providing maximum shoe sole flexibility particularly between the base of the calcaneus 125 (heel) and the metatarsal heads 126 (forefoot) along an axis 120. An unnatural torsion occurs about that axis if flexibility is insufficient so that a conventional shoe sole interferes with the inversion/eversion motion by restraining it. The object of the design is to allow the relatively more mobile (in eversion and inversion) calcaneus to articulate freely and independently from the relatively more fixed forefoot, instead of the fixed or fused structure or lack of stable structure between the two in conventional designs. In a sense, freely articulating joints are created in the shoe sole that parallel those of the foot. The design is to remove nearly all of the shoe sole material between the heel and the forefoot, except under one of the previously described essential structural support elements, the base of the fifth metatarsal 97. An optional support for the main longitudinal arch 121 may also be retained for runners with substantial foot pronation, although would not be necessary for many runners. The forefoot can be subdivided (not shown) into its component essential structural support and propulsion elements, the individual heads of the metatarsal and the heads of the distal phalanges, so that each major articulating joint set of the foot is paralleled by a freely articulating shoe sole support propulsion element, an anthropomorphic design; various aggregations of the subdivisions are also possible. An added benefit of the design is to provide better flexibility along axis 122 for the forefoot during the toe-off propulsive phase of the running stride, even in the absence of any other embodiments of the applicant's invention; that is, the benefit exists for existing conventional shoe sole designs.

FIG. 28A shows in sagittal plane cross section a specific design maximizing flexibility, with large nonessential sec-

tions removed for flexibility and connected by only a top layer (horizontal plane) of non-stretching fabric **123** like Dacron polyester or Kevlar. FIG. **28B** shows another specific design with a thin top sole layer **124** instead of fabric and a different structure for the flexibility sections: a design variation that provides greater structural support, but less flexibility though still much more than conventional designs. Not shown is a simple, minimalist approach, which is comprised of single frontal plane slits in the shoe sole material (all layers or part): the first midway between the base of the calcaneus and the base of the fifth metatarsal, and the second midway between that base and the metatarsal heads. FIG. **28C** shows a bottom view (horizontal plane) of the inversion/eversion flexibility design.

FIG. **29** is new in this continuation-in-part application and provides a means to measure the contoured shoe sole sides incorporated in the applicant's inventions described above. FIG. **29** is FIG. **27** modified to correlate the height or extent of the contoured side portions of the shoe sole with a precise angular measurement from zero to 180 degrees. That angular measurement corresponds roughly with the support for sideways tilting provided by the contoured shoe sole sides of any angular amount from zero degrees to 180 degrees, at least for such contoured sides proximate to any one or more or all of the essential stability or propulsion structures of the foot, as defined above in FIG. **21**. The contoured shoe sole sides as described in this application can have any angular measurement from zero degrees to 180 degrees.

Thus, it will clearly be understood by those skilled in the art that the foregoing description has been made in terms of the preferred embodiment and various changes and modifications may be made without departing from the scope of the present invention which is to be defined by the appended claims.

What is claimed is:

**1.** A sole of a shoe, comprising:

- a sole outer surface;
  - a sole inner surface for supporting a foot of an intended wearer;
  - a heel portion at a location substantially corresponding to a calcaneus bone of the foot of the intended wearer;
  - a midtarsal portion at a location substantially corresponding to a midtarsal of the foot of the intended wearer; and
  - a forefoot portion at a location substantially corresponding to a forefoot of the foot of the intended wearer;
- the sole heel, midtarsal, and forefoot portions having a sole medial side, a sole lateral side, and a sole middle portion between the sole sides, at least a part of the sole outer surface of the middle portion having a tread pattern:
- the sole lateral side and the sole medial side including a lowermost side section adjacent the middle portion, an intermediate side section above the lowermost side section, and an uppermost side section above the intermediate side section;
  - the heel portion having a lateral heel part at a location substantially corresponding to the lateral tuberosity of the calcaneus bone of the foot of the intended wearer, and a medial heel part at a location substantially corresponding to the base of the calcaneus bone of the foot of the intended wearer;
  - the midtarsal portion being between the forefoot portion and heel portion, and having a lateral midtarsal part at a location substantially corresponding to the base of a fifth metatarsal bone of the foot of the intended wearer;

the forefoot portion having a forward medial forefoot part at a location substantially corresponding to the head of the first distal phalange bone, a rear medial forefoot part at a location substantially corresponding to the head of a first metatarsal bone of the foot of the intended wearer, and a rear lateral forefoot part at a location substantially corresponding to the head of a fifth metatarsal bone of the foot of the intended wearer:

the shoe sole having at least one bulge, each at least one bulge including at least a concavely rounded portion of both the inner surface and the outer surface of the shoe sole, both as viewed in a shoe sole frontal plane during a shoe upright, unloaded shoe condition, the concavity existing with respect to the intended wearer's foot location in the shoe:

at least a part of said at least one bulge bounded by said concavely rounded surfaces including a midsole part and an outersole part;

a bulge being located at least at the lateral midtarsal part;

the concavely rounded outer surface portion of the bulge extending through the lowermost side section of at least one of the sole lateral side and the sole medial side, as viewed in a shoe sole frontal plane during a shoe upright, unloaded condition;

at least an uppermost portion of an outer surface of the bulge extending above a lowermost point of the sole inner surface, as viewed in a frontal plane during a shoe upright condition; and

a heel portion thickness that is greater than a forefoot portion thickness as viewed in a shoe sole sagittal plane;

the lateral midtarsal bulge outer surface forming a portion of the sole lateral side.

**2.** A sole according to claim **1**, wherein the concavely rounded bulge outer surface at the lateral midtarsal part also forms a portion of the sole middle portion.

**3.** A sole of a shoe, comprising:

- a sole outer surface;
  - a sole inner surface for supporting a foot of an intended wearer;
  - a heel portion at a location substantially corresponding to a calcaneus bone of the foot of the intended wearer;
  - a midtarsal portion at a location substantially corresponding to a midtarsal of the foot of the intended wearer; and
  - a forefoot portion at a location substantially corresponding to a forefoot of the foot of the intended wearer;
- the shoe sole heel, midtarsal and forefoot portions having a sole medial side, a sole lateral side, and a sole middle portion between the sole sides;
- the heel portion having a lateral heel part at a location substantially corresponding to the lateral tuberosity of the calcaneus bone of the foot of the intended wearer, and a medial heel part at a location substantially corresponding to the base of the calcaneus bone of the foot of the intended wearer;
  - the midtarsal portion being between the forefoot portion and heel portion, and having a lateral midtarsal part at a location substantially corresponding to the base of a fifth metatarsal bone of the foot of the intended wearer;
  - the forefoot portion having a forward medial forefoot part at a location substantially corresponding to the head of the first distal phalange bone, a rear medial forefoot

part at a location substantially corresponding to the head of a first metatarsal bone of the foot of the intended wearer, and a rear lateral forefoot part at a location substantially corresponding to the head of a fifth metatarsal bone of the foot of the intended wearer;

5 the shoe sole including bulges, a section of an outer surface of each bulge being concavely rounded as viewed in a shoe sole frontal plane during a shoe upright, unloaded condition, the concavity existing with respect to the intended wearer's foot location in the shoe;

10 a bulge being located at least at each of: the lateral heel part, the forward medial forefoot part, the rear medial forefoot part, the rear lateral forefoot part, and the lateral midtarsal part;

15 the bulges forming at least a portion of one of a bottom of the sole middle portion, the sole medial side, and the sole lateral side;

20 a first indentation between the rear lateral forefoot part bulge and the lateral midtarsal part bulge;

a second indentation between the lateral heel part bulge and the lateral midtarsal part bulge;

25 a third indentation between the forward medial forefoot part bulge and the rear medial forefoot part bulge; and

a heel portion thickness that is greater than a forefoot portion thickness, as viewed in a shoe sole sagittal plane.

4. A sole according to claim 3, further including a bulge at the medial heel part, the concavely rounded outer surface section thereof forming a portion of the sole medial side.

5. A sole of a shoe, comprising:

a sole outer surface;

35 a sole inner surface for supporting a foot of an intended wearer;

a heel portion at a location substantially corresponding to a calcaneus of the foot of the intended wearer;

a midtarsal portion at a location substantially corresponding to a midtarsal of the foot of the intended wearer;

40 and

a forefoot portion at a location substantially corresponding to a forefoot of the foot of the intended wearer;

45 the sole heel, midtarsal and forefoot portions having a sole medial side and a sole lateral side;

50 the heel portion having a lateral heel part at a location substantially corresponding to the lateral tuberosity of the calcaneus of the foot of the intended wearer, and a medial heel part at a location substantially corresponding to the base of the calcaneus of the foot of the intended wearer;

55 the midtarsal portion being between the forefoot portion and heel portion, and having a lateral midtarsal part at a location substantially corresponding to the base of a fifth metatarsal of the foot of the intended wearer;

60 the forefoot portion having a forward medial forefoot part at a location substantially corresponding to the head of the first distal phalange, a rear medial forefoot part at a location substantially corresponding to the head of a first metatarsal of the foot of the intended wearer, and a rear lateral forefoot part at a location substantially corresponding to the head of a fifth metatarsal of the foot of the intended wearer;

65 the sole including a concavely rounded first bulge at the forward medial forefoot part as viewed in a shoe sole frontal plane, the concavity existing with respect to the intended wearer's foot location in the shoe;

a second bulge at one of the rear lateral and medial forefoot parts; and

a transverse indentation in the sole outer surface, between the forward medial forefoot part bulge and the second bulge,

the bulges being contoured at the sole inner surface so that the sole extends upwardly at at least one of the lateral and medial side for conforming with at least part of a side of the foot of the intended wearer; and

a heel portion thickness that is greater than a forefoot portion thickness as viewed in a sagittal plane.

6. A sole of a shoe, comprising:

a sole outer surface;

a sole inner surface for supporting a foot of an intended wearer;

a heel portion at a location substantially corresponding to a calcaneus bone of the foot of the intended wearer;

a midtarsal portion at a location substantially corresponding to a midtarsal of the foot of the intended wearer; and

a forefoot portion at a location substantially corresponding to a forefoot of the foot of the intended wearer;

the sole heel, midtarsal, and forefoot portions having a medial side, a lateral side, and a sole middle portion between the sole sides;

the heel portion having a lateral heel part at a location substantially corresponding to the lateral tuberosity of the calcaneus bone of the foot of the intended wearer, and a medial heel part at a location substantially corresponding to the base of the calcaneus bone of the foot of the intended wearer;

the midtarsal portion being between the forefoot portion and heel portion, and having a lateral midtarsal part at a location substantially corresponding to the base of a fifth metatarsal bone of the foot of the intended wearer;

the forefoot portion having a forward medial forefoot part at a location substantially corresponding to the head of the first distal phalange bone, a rear medial forefoot part at a location substantially corresponding to the head of a first metatarsal bone of the foot of the intended wearer, and a rear lateral forefoot part at a location substantially corresponding to the head of a fifth metatarsal bone of the foot of the intended wearer;

the shoe sole having bulges, each bulge including a concavely rounded section of the outer sole surface, as viewed in a shoe sole frontal plane during a shoe upright, unloaded condition, the concavity existing with respect to the intended wearer's foot location in the shoe;

a bulge being located at least at each of: the rear medial forefoot part, the rear lateral forefoot part, and the lateral midtarsal part;

each bulge forming a concave portion of at least one of the sole medial side and the sole lateral side;

the heel portion including a concavely rounded portion about the sole lateral side, the sole medial side, and a bottom of the sole middle portion, as viewed in a shoe sole frontal plane during a shoe upright, unloaded condition, the concavity existing with respect to an intended wearer's foot location in the shoe;

an indentation between the lateral midtarsal part and heel portion; and

a heel portion thickness that is greater than a forefoot portion thickness as viewed in a shoe sole sagittal plane.

## 19

7. A sole of a shoe, comprising:  
 a sole outer surface;  
 a sole inner surface for supporting a foot of an intended  
 wearer;  
 a heel portion at a location substantially corresponding to 5  
 a calcaneus bone of the foot of the intended wearer;  
 a midtarsal portion at a location substantially correspond-  
 ing to a midtarsal of the foot of the intended wearer;  
 and  
 a forefoot portion at a location substantially correspond- 10  
 ing to a forefoot of the foot of the intended wearer;  
 the sole heel, midtarsal, and forefoot portions having a  
 sole medial side, a sole lateral side, and a sole middle  
 portion between the sole sides, at least a part of the sole  
 outer surface of the middle portion having a tread 15  
 pattern:  
 the sole lateral side and the sole medial side including  
 a lowermost side section adjacent the middle portion,  
 an intermediate side section above the lowermost  
 side section, and an uppermost side section above the 20  
 intermediate side section;  
 the heel portion having a lateral heel part at a location  
 substantially corresponding to the lateral tuberosity  
 of the calcaneus bone of the foot of the intended  
 wearer, and a medial heel part at a location substan- 25  
 tially corresponding to the base of the calcaneus  
 bone of the foot of the intended wearer;  
 the midtarsal portion being between the forefoot por-  
 tion and heel portion, and having a lateral midtarsal  
 part at a location substantially corresponding to the 30  
 base of a fifth metatarsal bone of the foot of the  
 intended wearer;  
 the forefoot portion having a forward medial forefoot  
 part at a location substantially corresponding to the 35  
 head of the first distal phalange bone, a rear medial  
 forefoot part at a location substantially correspond-  
 ing to the head of a first metatarsal bone of the foot  
 of the wearer, and a rear lateral forefoot part at a  
 location substantially corresponding to the head of a 40  
 fifth metatarsal bone of the foot of the intended  
 wearer;  
 the shoe sole further having bulges, each bulge including  
 at least a concavely rounded portion of both the inner  
 surface and the outer surface of the shoe sole, both as 45  
 viewed in a shoe sole frontal plane during a shoe  
 upright, unloaded shoe condition, the concavity exist-  
 ing with respect to the intended wearer's foot location  
 in the shoe;  
 at least a part of each bulge bounded by said concavely  
 rounded surfaces including a midsole part and an 50  
 outersole part;  
 a bulge being located at least at the medial heel part and  
 the lateral heel part;  
 the concavely rounded outer surface of each bulge  
 extending through the lowermost side section of at 55  
 least one of the sole lateral side and the sole medial  
 side, as viewed in a shoe sole frontal plane during a  
 shoe sole upright, unloaded condition;  
 at least an uppermost portion of a sole outer surface of  
 each bulge extending above a lowermost point of the 60  
 sole inner surface, as viewed in a frontal plane during  
 a shoe upright condition;  
 a heel portion thickness that is greater than a forefoot  
 portion thickness as viewed in a shoe sole sagittal  
 plane; and 65  
 an indentation located between the lateral midtarsal part  
 and the heel part bulges.

## 20

8. A sole of a shoe, comprising:  
 a sole outer surface:  
 a sole inner surface for supporting a foot of an intended  
 wearer;  
 a heel portion at a location substantially corresponding to  
 a calcaneus bone of the foot of the intended wearer;  
 a midtarsal portion at a location substantially correspond-  
 ing to a midtarsal of the foot of the intended wearer;  
 and  
 a forefoot portion at a location substantially correspond-  
 ing to a forefoot of the foot of the intended wearer;  
 the sole heel, midtarsal, and forefoot portions having a  
 sole medial side, a sole lateral side, and a sole middle  
 portion between the sole sides, at least a part of the sole  
 outer surface of the middle portion having a tread  
 pattern;  
 the sole lateral side and the sole medial side including  
 a lowermost side section adjacent the middle portion,  
 an intermediate side section above the lowermost  
 side section, and an uppermost side section above the 20  
 intermediate side section;  
 the heel portion having a lateral heel part at a location  
 substantially corresponding to the lateral tuberosity  
 of the calcaneus bone of the foot of the intended  
 wearer, and a medial heel part at a location substan- 25  
 tially corresponding to the base of the calcaneus  
 bone of the foot of the intended wearer;  
 the midtarsal portion being between the forefoot por-  
 tion and heel portion, and having a lateral midtarsal  
 part at a location substantially corresponding to the 30  
 base of a fifth metatarsal bone of the foot of the  
 intended wearer;  
 the forefoot portion having a forward medial forefoot  
 part at a location substantially corresponding to the 35  
 head of the first distal phalange bone, a rear medial  
 forefoot part at a location substantially correspond-  
 ing to the head of a first metatarsal bone of the foot  
 of the wearer, and a rear lateral forefoot part at a  
 location substantially corresponding to the head of a 40  
 fifth metatarsal bone of the foot of the intended  
 wearer;  
 the shoe sole having at least one bulge, each at least one  
 bulge including at least a concavely rounded portion of  
 both the inner surface and the outer surface of the shoe  
 sole, both as viewed in a shoe sole frontal plane during  
 a shoe upright, unloaded shoe condition, the concavity  
 existing with respect to the intended wearer's foot  
 location in the shoe;  
 at least a part of said at least one bulge bounded by said  
 concavely rounded surfaces including a midsole part  
 and an outersole part;  
 said at least one bulge being located at least at one of  
 the forward medial forefoot part and the rear medial  
 forefoot part;  
 the concavely rounded outer surface of each at least one  
 bulge extending through the lowermost side section  
 of at least one of the sole lateral side and the sole  
 medial side, as viewed in a shoe sole frontal plane  
 during a shoe upright, unloaded condition;  
 at least an uppermost portion of an outer surface of each  
 at least one bulge extending above a lowermost point  
 of the sole inner surface, as viewed in a frontal plane  
 during a shoe upright condition;  
 a heel portion thickness that is greater than a forefoot  
 portion thickness as viewed in a shoe sole sagittal  
 plane; and

## 21

said at least one bulge includes at least a part with said outer surface being concavely rounded below one of the forefoot parts, as viewed in a sagittal plane, during a shoe unloaded, upright condition, the concavity existing with respect to the intended wearer's foot location in the shoe. 5

9. A sole of a shoe, comprising:

a sole outer surface;  
a sole inner surface for supporting a foot of an intended wearer; 10

a heel portion at a location substantially corresponding to a calcaneus bone of the foot of the intended wearer;

a midtarsal portion at a location substantially corresponding to a midtarsal of the foot of the intended wearer; and 15

a forefoot portion at a location substantially corresponding to a forefoot of the foot of the intended wearer;

the sole heel, midtarsal, and forefoot portions having a sole medial side, a sole lateral side, and a sole middle portion between the sole sides, at least a part of the sole outer surface of the middle portion having a tread pattern: 20

the sole lateral side and the sole medial side including a lowermost side section adjacent the middle portion, an intermediate side section above the lowermost side section, and an uppermost side section above the intermediate side section; 25

the heel portion having a lateral heel part at a location substantially corresponding to the lateral tuberosity of the calcaneus bone of the foot of the intended wearer, and a medial heel part at a location substantially corresponding to the base of the calcaneus bone of the foot of the intended wearer; 30

the midtarsal portion being between the forefoot portion and heel portion, and having a lateral midtarsal part at a location substantially corresponding to the base of a fifth metatarsal bone of the foot of the intended wearer; 35

the forefoot portion having a forward medial forefoot part at a location substantially corresponding to the head of the first distal phalange bone, a rear medial forefoot part at a location substantially corresponding to the head of a first metatarsal bone of the foot of the wearer, and a rear lateral forefoot part at a location substantially corresponding to the head of a fifth metatarsal bone of the foot of the intended wearer; 40 45

the shoe sole having at least one bulge, each at least one bulge including at least a concavely rounded portion of both the inner surface and the outer surface of the shoe sole, both as viewed in a shoe sole frontal plane during a shoe upright, unloaded condition, the concavity existing with respect to the intended wearer's foot location in the shoe: 50

at least a part of each said at least one bulge bounded by said concavely rounded surfaces including a midsole part and an outsole part; 55

said at least one bulge being located at least at one of: the forward medial forefoot part, the rear medial forefoot part, the rear lateral forefoot part, the lateral midtarsal part, the medial heel part, and the lateral heel part; 60

the concavely rounded outer surface of each at least one bulge extending through the lowermost side section of at least one of the sole lateral side and the sole medial side, as viewed in a shoe sole frontal plane during a shoe upright, unloaded condition; 65

## 22

at least an uppermost portion of an outer surface of each said at least one bulge extending above a lowermost point of the sole inner surface, as viewed in a frontal plane during a shoe upright condition;

a heel portion thickness that is greater than a forefoot portion thickness as viewed in a shoe sole sagittal plane; and

said at least one bulge including at least a part with said outer surface being concavely rounded below the forward medial forefoot part, as viewed in a sagittal plane during a shoe upright, unloaded condition, the concavity existing with respect to the intended wearer's foot location in the shoe.

10. The shoe sole according to claim 8, wherein said at least one bulge includes at least a part with said inner surface being concavely rounded below one of the forefoot parts, as viewed in a shoe sole sagittal plane, the concavity existing with respect to the intended wearer's foot location in the shoe. 15

11. A sole of a shoe, comprising:

a sole outer surface;

a sole inner surface for supporting a foot of an intended wearer;

a heel portion at a location substantially corresponding to a calcaneus bone of the foot of the intended wearer;

a midtarsal portion at a location substantially corresponding to a midtarsal of the foot of the intended wearer; and 20

a forefoot portion at a location substantially corresponding to a forefoot of the foot of the intended wearer;

the sole heel, midtarsal, and forefoot portions having a sole medial side, a sole lateral side, and a sole middle portion between the sole sides, at least a part of the sole outer surface of the middle portion having a tread pattern: 25

the sole lateral side and the sole medial side including a lowermost side section adjacent the middle portion, an intermediate side section above the lowermost side section, and an uppermost side section above the intermediate side section;

the heel portion having a lateral heel part at a location substantially corresponding to the lateral tuberosity of the calcaneus bone of the foot of the intended wearer, and a medial heel part at a location substantially corresponding to the base of the calcaneus bone of the foot of the intended wearer;

the midtarsal portion being between the forefoot portion and heel portion, and having a lateral midtarsal part at a location substantially corresponding to the base of a fifth metatarsal bone of the foot of the intended wearer; 30

the forefoot portion having a forward medial forefoot part at a location substantially corresponding to the head of the first distal phalange bone, a rear medial forefoot part at a location substantially corresponding to the head of a first metatarsal bone of the foot of the wearer, and a rear lateral forefoot part at a location substantially corresponding to the head of a fifth metatarsal bone of the foot of the intended wearer; 35 40 45

the shoe sole having bulges, each bulge including at least a concavely rounded portion of both the inner surface and the outer surface of the shoe sole, both as viewed in a shoe sole frontal plane during a shoe upright, unloaded shoe condition, the concavity existing with respect to the intended wearer's foot location in the shoe: 40 45



23

at least a part of each bulge bounded by said concavely rounded surfaces including a midsole part and an outersole part;  
 said bulges being located at least at the rear medial forefoot part and the rear lateral forefoot part;  
 the concavely rounded outer surface of the bulges extending through the lowermost side section of at least one of the sole lateral side and the sole medial side, as viewed in a shoe sole frontal plane during a shoe upright, unloaded condition;  
 at least an uppermost portion of an outer surface of the bulge extending above a lowermost point of the sole inner surface, as viewed in a frontal plane during a shoe upright condition:

a heel portion thickness that is greater than a forefoot portion thickness as viewed in a shoe sole sagittal plane; and

at least one convexly rounded groove located between said rear forefoot parts as viewed in a shoe sole frontal plane during a shoe upright condition, the convexity existing with respect to the intended wearer's foot location in the shoe.

12. The shoe sole according to claim 11, including a bulge located at the lateral heel part.

13. The shoe sole according to claim 11, including a bulge located at the medial heel part.

14. A sole of a shoe, comprising:

a sole outer surface;

a sole inner surface for supporting a foot of an intended wearer;

a heel portion at a location substantially corresponding to a calcaneus bone of the foot of the intended wearer;

a midtarsal portion at a location substantially corresponding to a midtarsal of the foot of the intended wearer; and

a forefoot portion at a location substantially corresponding to a forefoot of the foot of the intended wearer;

the sole heel, midtarsal, and forefoot portions including a sole medial side, a sole lateral side, and a sole middle portion between the two sole sides, at least a part of an outer surface of the middle portion having a tread pattern;

a lateral heel part at a location substantially corresponding to the lateral tuberosity of the calcaneus bone of the foot of the intended wearer; and

a medial heel part at a location substantially corresponding to the base of the calcaneus bone of the foot of the intended wearer;

the midtarsal portion being between the forefoot portion and heel portion, and having a lateral midtarsal part at a location substantially corresponding to the base of a fifth metatarsal bone of the foot of the intended wearer and a medial midtarsal part at a location substantially corresponding to the main longitudinal arch of the foot of the intended wearer;

the forefoot portion having a forward medial forefoot part at a location substantially corresponding to the head of the first distal phalange bone, a rear medial forefoot part at a location substantially corresponding to the head of a first metatarsal bone of the foot of the intended wearer, and a rear lateral forefoot part at a location substantially corresponding to the head of a fifth metatarsal bone of the foot of the intended wearer;

the shoe sole having at least one bulge, at least a portion of both an inner surface and an outer surface of each bulge being concavely rounded, both as viewed in a shoe sole frontal plane during a shoe upright, unloaded

24

condition, the concavity existing with respect to the intended wearer's foot location in the shoe;

at least a part of said at least one bulge bounded by said concavely rounded surfaces including a midsole part and an outersole part;

one said at least one bulge being located at the lateral midtarsal part;

the outer surface of the lateral midtarsal part bulge including an uppermost section extending above a lowest point of said sole inner surface, as viewed in a shoe sole frontal plane during a shoe upright, unloaded condition; and

a heel portion having a greater thickness than a forefoot portion, as viewed in a shoe sole sagittal plane.

15. The shoe sole according to claim 14, wherein said lateral midtarsal part bulge extends to a bottom of the middle portion as viewed in a shoe sole frontal plane during a shoe upright condition.

16. The shoe sole according to claim 14, wherein said outer surface of the shoe sole includes a convexly rounded portion, as viewed in a shoe sole sagittal plane during a shoe upright, unloaded condition, the convexity existing with respect to the intended wearer's foot location in the shoe and;

said convexly rounded portion forming an arch that is located adjacent the medial midtarsal part.

17. The shoe sole according to claim 14, wherein the lateral midtarsal bulge includes a thickness that tapers from a greatest thickness to a least thickness on each opposing extent of the bulge, as viewed in a shoe sole horizontal plane during a shoe upright condition.

18. A sole according to claim 14, including a bulge located at the forward medial forefoot part.

19. A sole according to claim 14, including a bulge located at the rear medial forefoot part.

20. A sole according to claim 14, including a bulge located at the rear lateral forefoot part.

21. A sole according to claim 14, including a bulge located at the medial heel part.

22. A sole according to claim 14, including a bulge located at the lateral heel part.

23. The shoe sole according to claim 16, wherein said inner surface of the shoe sole includes a convexly rounded portion, as viewed in a shoe sole sagittal plane during a shoe upright, unloaded condition, the convexity existing with respect to the intended wearer's foot location in the shoe.

24. A sole according to claim 6, including one said bulge at the forward medial forefoot part.

25. A sole according to claim 6, including an indentation between the lateral midtarsal and rear lateral forefoot part bulges.

26. A sole according to claim 25, including a further bulge at the forward medial forefoot part, the concavely rounded outer surface section thereof forming a portion of the sole medial side and the middle portion, and a further indentation between the forward medial forefoot part bulge and the rear medial forefoot part bulge.

27. A sole according to claim 3, wherein the concavely rounded bulge at the lateral heel part forms a portion of the lateral side and the middle portion of the heel portion.

28. A shoe sole according to claim 5, wherein the second bulge is located at the rear medial forefoot part, and the transverse indentation is located between the rear medial forefoot part bulge and the forward medial forefoot part bulge.

29. A sole according to claim 14, including a bulge at the rear medial forefoot part, the concavely rounded outer surface of the medial forefoot part bulge forming a portion of the sole medial side.

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 6,115,941  
DATED : September 12, 2000  
INVENTOR(S) : Frampton E. Ellis, III

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 16, claim 2,

Line 36, change "concanely," to -- concavely --.

Column 24, claim 16,

Line 22, change "and;" to -- ; and --.

Signed and Sealed this

Eleventh Day of December, 2001

Attest:

*Nicholas P. Godici*

Attesting Officer

NICHOLAS P. GODICI  
Acting Director of the United States Patent and Trademark Office

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 6,115,941  
DATED : September 12, 2000  
INVENTOR(S) : Frampton E. Ellis, III

Page 1 of 3

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page.

Item [56], **References Cited**, U.S. PATENT DOCUMENTS, please insert:

--	5,544,429	8/1996	Ellis, III
	4,468,870	9/1984	Sternberg
	4,259,792	4/1981	Halberstadt
	2,170,652	8/1939	Brennan
	4,748,753	6/1988	Ju
	4,949,476	8/1990	Anderie
	4,559,724	12/1985	Norton
	4,641,438	2/1987	Laird et al.
	2,179,942	11/1939	Lyne --

FOREIGN PATENT DOCUMENTS, please insert:

--	2 706 645	8/1978	Germany
	2 805 426	8/1979	Germany
	3 317 462	10/1983	Germany
	88/08263	11/1988	WIPO
	3 245 182	5/1983	Germany
	238995	9/1987	EPO
	87/07480	12/1987	WIPO
	1138194	12/1982	Canada --

Column 3.

Line 32, delete "and" (second occurrence);  
Line 48, delete "11E"; and  
Line 56, change "shows" to -- show --.

Column 4.

Line 7, change "in" to -- In --;  
Line 11, delete "line 26, after "arch;" add";  
Line 18, change "plan" to -- plane --;  
Line 24, change "FIGS. 20D and 20E" to -- FIG. 20D -- and change "sagittal" to -- sagittal --;  
Line 29, after "22A" delete "and 22B"; and  
Line 53, change "FIGS. 28B and 28C" to -- FIG. 28B --.

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 6,115,941  
DATED : September 12, 2000  
INVENTOR(S) : Frampton E. Ellis, III

Page 2 of 3

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 7,

Line 45, change "applicants" to -- applicant's --.

Column 8,

Line 3, change "remain" to -- remains --.

Column 9,

Line 15, change "become" to -- becomes --;

Line 25, change "93" to -- 39 --; .

Line 61, change "individuals" to -- individual's --; and

Line 67, change "individuals" to -- individual's --.

Column 10,

Line 49, after "for" insert -- the --; and

Line 56, change "FIGS." to -- FIG. --.

Column 12,

Lines 40-42, delete "--"; Line 19, after "reversed" insert — as shown at the downwardly convex rounded bulges **95a**, **96c**, **96g**, **97b** and **98a** of the outer surface of the sole member"; and

Line 52, after "reversed" insert -- as shown at the downwardly convex rounded bulges **95a**, **96c**, **96g**, **97b** and **98a** of the outer surface of the sole member --.

Column 14,

Line 3, after "lines" delete "."; and

Line 56, change "metatarsal" to -- metatarsals --.

Column 18,

Line 4, delete "the" (first occurrence).

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 6,115,941  
DATED : September 12, 2000  
INVENTOR(S) : Frampton E. Ellis, III

Page 3 of 3

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 19,


Line 42, after "sole" delete "further";  
Line 46, after "unloaded" delete "shoe"; and  
Line 58, after "shoe" delete "sole".

Column 24,

Line 26, after "midtarsal" insert -- part -- .

Signed and Sealed this

Tenth Day of December, 2002

A handwritten signature in black ink, appearing to read "James E. Rogan", written over a horizontal line.

JAMES E. ROGAN  
*Director of the United States Patent and Trademark Office*